

Exhaust Hose Reel 865 - Electric Motor Driven

Electric Motor Driven Exhaust Hose Reel



The best solution in workshops with a high ceiling, where overhead cranes etc. have to be considered, or where high vehicles must pass. Operated via a hand unit either an IR control or pendant control. A receiving eye on the reel shows the status of operation. Electronic upper and lower limit switches reduce the risk of malfunction and unnecessary wearing of the hose. Fan start/stop is automatically controlled. Mounting of fan on reel is possible. No programming is lost when a power failure occurs. If the power is cut, the electro-magnetic brake will lock the drum instantly.

- Convenient and safe operation
- Automatic fan for energy savings
- Quick & easy installation reduces cost
- Settings for limit switches made from floor level
- Compact, modern design

| | |
|------------------------|--|
| Product name | Exhaust Hose Reel 865 - Electric Motor Driven |
| Installation | [Indoor] |
| Material recycling (%) | 100 |
| Operating Temperature | -10 to +50C |
| Further technical data | Max lifting capacity: 30kg Power supply: 325 VA |
| Power Voltage (V) | 100-230 |
| Frequency (Hz) | 50/60 |
| No of phases | 1 |
| Colour | Blue |
| Body type | [wide] |
| Electric/Spring driven | Electric motor |



Exhaust Hose Reel 865 - Electric Motor Driven






| Type of hose ¹ | Delivered with hose | Diameter, hose (mm) | Hose length (m) | Weight (kg) | Max hose length | Model |
|---------------------------|---------------------|---------------------|-----------------|-------------|-----------------|-----------|
| NR-CP | Yes | 100 | 7,5 | 41-49 | 12,5 | 20802965 |
| NFC-3 | Yes | 100 | 7,5 | 41-49 | 12,5 | 20803065 |
| NR-CP | Yes | 125 | 7,5 | 41-49 | 10 | 20803365 |
| NFC-3 | Yes | 125 | 7,5 | 41-49 | 10 | 20803465 |
| NFC-3 | Yes | 150 | 7,5 | 41-49 | 10 | 20803865 |
| NR-CP | Yes | 150 | 10 | 41-49 | 10 | 20803965 |
| | No | 100 | | 32 | 12,5 | 20802665 |
| | No | 125 | | 32 | 10 | 20802765 |
| | No | 150 | | 32 | 10 | 20802865 |
| | No | 200 | | 40 | 7 | 20809165* |

*Max hose length 7,5m coiled, Max weight of hose including nozzle 30 kg.

¹ See table below

| Hose type | Specification | Temperature range, °C | Hose fittings in free hose end, distribution hose | Hose fitting on free hose end, inlet hose | Hose connection on reel, distribution hose | Hose connection on reel, inlet hose |
|-----------|---|--|---|---|--|-------------------------------------|
| NRCP | Polyester fabric, EPDM/PP coated. Helix in Polyester with EPDM cover. Max bending radius 225mm (inside) | -40 to +150 Deg. C (Inttermittent +170 Deg. C) | | | | |
| NFC3 | High temperature kevlar based material. Helix in galvanised steel. | -60 to +300 Deg. C (Inttermittent +350 Deg. C) | | | | |

Exhaust Hose Reel 865 - Electric Motor Driven

| | Accessory | Part No |
|---|---------------------------------------|----------|
|  | Pendant control incl. cable bracket | 20373712 |
|  | Transmitter with wall bracket | 20373522 |
|  | Stand for fan | 20373556 |
|  | Transformer 230/250 V to 24 V. 75 VA. | 10361560 |
|  | Transformer 230/250 V to 24 V. 25 VA. | 10363189 |

Exhaust Hose Reel 865 - Electric Motor Driven

