

Hose Reel 876

Welding reel designed for maximum safety in oxygen and acetylene welding applications.









The Hose Reel 876 represents the ultimate solution for oxygen & acetylene or oxygen & LPG welding in terms of safety, durability and easy handling.

- Well ventilated, single layer hose feed and storage - highest safety and easy handling without tangles.
- Open design for easy servicing
- Four-way roller guides prevent hose wear.
- Flexible - Easy to install on wall, floor or ceiling.
- Compliant with EU directives.


Product name	Hose Reel 876
Connection hose length (m)	1
Max working pressure (Mpa)	2
Corrosion resistance	Standard
Electric/Spring driven	Spring



Hose Reel 876

Image	Description	Media	Delivered with hose	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Model
	Hose reel Ser. 876 with 15m 1/4-3/8"	Oxygene & Acetylene	Yes	15	1x6,3 mm and 1x10 mm	1x6,3 mm and 1x10 mm	30831076
	Hose reel Ser. 876 with 18m 2x1/4"	Oxygene & Acetylene	Yes	18	6,3	6,3	30831176
	Hose reel Ser. 876 with 15m 3/8-3/8"	Oxygene & LPG	Yes	15	10	10	30831276
	Hose reel Ser. 876 with 15m 3/8-3/8"	Oxygene & Acetylene	Yes	15	10	10	30831376
	Hose reel Ser. 876 for 18m 2x1/4"	Oxygene & Acetylene	No				30831776
	Hose reel Series 876 for 15m 3/8-3/8" twin hose	Oxygene & Acetylene Oxygene & LPG	No				30831876

Hose Reel 876

Accessory		Part No
	Pivoting bracket.	30372407

Hose Reel 876

