

Hose Reel 886 Stainless

Stainless steel hose reel when corrosive resistance is required ideal for food processing industries.



This stainless steel hose reel, made entirely of stainless steel, is designed specifically for the food processing industry. It is very easy to clean thanks to rounded edges and features an easy to dismantle hose outlet, an externally mounted swivel, and a minimum number of material joints.

- Unique design makes easy cleaning
- Up to 25 m (82 ft.) hose capacity
- Meets international hygienic requirement

Product name	Hose Reel 886 Stainless
Connection hose length (ft)	-
Delivered with hose	No
Colour	Stainless
Corrosion resistance	Stainless steel
Electric/Spring driven	Spring




Hose Reel 886 Stainless

Image	Description	Type of hose ¹	Media	Distribution hose length (ft)	Diameter, connection hose (in)	Distribution hose diameter (in)	Max working pressure (psi)	Weight (lbs)	Max hose length	Model
			Water			1/2	1450	62	82	32800386*
			Water high pressure	82		3/8	3625	62	82	30801386
			Water	82		1/2	1450	62	82	30800386
			Water	59		3/4	290	62	59	30800186
			Water	33		25	290	62	33	30802186
			Water/Steam			19	0,6 (Steam, 160 °C) 2,0 (Water)	28	18	30805286
			Water/Steam			25	0,6 (Steam, 160 °C) 2,0 (Water)	28	10	30805086
	Connection Hose (1m)	I	Water		12,5		290	1		30344854**
	Connection Hose (1m)	G	Water high pressure		10		25			30344852***
	Connection Hose (1m)	H	Water high pressure		10		25			30373669*** *
	Connection Hose (1m)	E	Water ,Food		12,5		2			30373670***
	Connection Hose (1m)	E	Water ,Food		19		2			30373674***
	Connection Hose (1m)	E	Water ,Food		25		2			30373664***
	Connection Hose (1m)	F	Water ,Food		19		2			30373675****
	Connection Hose (1m)	F	Water ,Food		12,5		2			30373671****

Hose Reel 886 Stainless

Image	Description	Type of hose ¹	Media	Distribution hose length (ft)	Diameter, connection hose (in)	Distribution hose diameter (in)	Max working pressure (psi)	Weight (lbs)	Max hose length	Model
	Connection Hose (1m)	F	Water ,Food		25		2			30373666*** *
	Connection Hose (1m)	N	Water/Steam		25		0,6			30377081
	Connection Hose (1m)	N	Water/Steam		19		0,6			30377082
	Distribution hose	G	Water high pressure	25		10	25			30371900***
	Distribution hose	H	Water high pressure	25		10	25			30371953****
	Distribution hose	I	Water			12,5	290			30377078**** *
	Distribution hose	E	Water ,Food	25		12,5	2			30371898***
	Distribution hose	E	Water ,Food	18		19	2			30371897***
	Connection Hose (1m)	E	Water ,Food	10		25	2			30373663***
	Distribution hose	F	Water ,Food	25		12,5	2			30371951****
	Distribution hose	F	Water ,Food	18		19	2			30371950****
		F	Water ,Food	10		25	2			30373665*** *
	Distribution hose	N	Water/Steam			19	0,6			30377080
	Distribution hose	N	Water/Steam			25	0,6			30377079
			Compressed air ,Water			10	218	62	59	32800186

Hose Reel 886 Stainless

Image	Description	Type of hose ¹	Media	Distribution hose length (ft)	Diameter, connection hose (in)	Distribution hose diameter (in)	Max working pressure (psi)	Weight (lbs)	Max hose length	Model
			Water high pressure			12.5	3625	62	82	32801386

*NPT

**Galvanized fittings

***With galvanized steel fittings
















****With stainless steel fittings

*****Galvanized fittings for reel 886

¹ See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, chrome plated. With rubber hose grip	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
H	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, stainless steel. With rubber hose grip	Female 60° cone, stainless steel	Male 60° cone	Male 60° cone
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Synthetic textile braid	-30 - 100	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
F	Cover in NBR/PVC and inner tube in food grade quality NBR. Synthetic textile braid	-20 - 100	Male 60° cone, stainless steel	Female 60° cone, stainless steel	Male 60° cone	Male 60° cone
N		-20 - 164				

Hose Reel 886 Stainless

	Accessory	Part No
	Pivoting Wall bracket Stainless Steel	30373668
	Roller guide.	30341550
	Water gun in chromium plated brass	30400110
	Water gun in stainless steel 316	30400210
	Water gun EX	30400211
	Water gun in stainless steel 316	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl. 1/2(m)-3/8(f) brass	30431510
	Swivl. coupl. 1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010

Hose Reel 886 Stainless

