

Cable Reel 793

The power cable reel 793 is a robust and comes in 1-phase and 3-phase and is supplied with thermal overload protector.



A heavy duty cable reel for use in industrial environments. The cable reel is available in 1-phase and 3-phase versions and supplied with thermal overload protector.

The Nederman cable reel 793 accommodates power cable lengths up to 25 m (82 ft.). The cable reel components are made of composite materials and galvanized steel.

- Degree of protection code: IP 55
- Tested and approved according to IEC 61316
- Rubber power cable

Product name	Cable Reel 793
Electric plug	without
Media	[power]
Colour	Black
Connection cable, Length (m)	1
Weight (kg)	15
Distribution cable, type	H07RN-F
Corrosion resistance	Standard
Electric/Spring driven	Spring



Cable Reel 793

Power Voltage (V)	No of phases	Amperage (A)	Conductors (No. x mm ²)	Distribution cable length (m)	Connection cable (No. x mm ²)	Power (kW)	Max Power (kW) when cable coiled	[model]
230	1	16	3Gx2,5	18	3G2,5	3,8	2,3	30700293
230	1	16	3Gx2,5	25	3G2,5	3,8	2,3	30700493
400	3	10	5Gx2,5	15	5G2,5	6,9	5,5	30701293
400	3	10	5Gx2,5	22	5G2,5	6,9	5,5	30701493

Cable Reel 793

