

Air Purification Box CCD-1RC

CCD-1RC is design for free hanging applications to control light airborne dust/smoke in a contaminated air stream.



Produkt namn	Air Purification Box CCD-1RC
Ljudnivå (dB(A))	75,6
Filter avskiljningsgrad (%)	95
Tryckluftsförbrukning	
Installation	Inomhus
Metod för filterrensning	Engångsfilter
Applikation	Stoft, Rök
Kapacitet (max luftflöde m ³ /h)	2550
Temperaturområde	Max. temperature of filtered media 80 Deg. C.
Matningsspänning (V)	230
Frekvens (Hz)	50
Vikt (kg)	51
Effekt (kW)	0,33



Rök



Stoft




Air Purification Box CCD-1RC

Beskrivning	Model
Air purification box without indicator	73000067
Air purification box with indicator	73000071

Air Purification Box CCD-1RC


Tillbehör		Artikelnummer
	Filter 595 x 595 x 98 G4 (LJ10004)	73000094
	Bag Filter 595 x 595	73000095

Air Purification Box CCD-1RC



Function

The function of the machinery is that the airborne particulate is drawn by the fan (pos. 1) into the air cleaner and through the filters (pos. 2) located at the front of the unit. The cleaned air is discharged at the rear of the unit via a double deflection grill (pos. 3).



Dimensions