


## Magna Track HS

Uitlaatgasafzuiging voor hulpposten met hoge frequentie / hoge snelheid runs



De MagnaTrack HS is ontworpen om hulpposten te bedienen met een hoge frequentie van runs. Het baansysteem dient voor een voertuig tegelijk. De stabilisator heeft een constant hefvermogen. MagnaTrack HS is beschikbaar in lengten van 3,5 tot 18 m; (10 tot 60 ft) en past op voertuigen met laag en hoog gemonteerde uitlaatpijpen.

Capaciteit: 1 voertuig per systeem

Uitlaatpijpen: Hoge of lage uitlaatpijpen

Hoge uitgangssnelheid tot 25 km/h - 15 mph

Voor achterruit (of in beweging)

Optionele automatisch start/stop apparaat dat het volgende biedt:

- Praktische besturing van de ventilator start/stop
- Veilige besturing van luchtkwaliteit (bronventilatie start automatisch wanneer de motor van het voertuig start)
- Eenvoudige programmering
- Goedkeuring voor radio-apparatuur volgens EC-richtlijnen, FCC (VS) en IC (Canada)

- Capacity: 1 vehicle per system
- Exhaust pipes: High level or Low level tail pipes
- High exit speed: up to 25 km/h; 15 mp
- For reverse-in (or drive-through)
- Optional automatic start/stop device that offers:
  - Practical control of fan start/stop
  - Safe control of air quality (source ventilation automatically starts when vehicle engine starts)
  - Simple programming
  - Approval for radio equipment acc. to EC directives, FCC (USA) and IC (Canada)

Product naam	Magna Track HS
--------------	----------------







## Magna Track HS

Afbeelding	Naam voor Datasheet	Slangdiameter (m)	Slanglengte (m)	Model
	MagnaTrack Horizontal 3,5m (12')	160		20804164*
	MagnaTrack Horizontal 5,9m (20')	160		20804264*
	MagnaTrack Horizontal 9,5m (32')	160		20804364*
	MagnaTrack Horizontal 11,8m (39')	160		20804464*
	MagnaTrack Horizontal 15,3m (51')	160		20804564*
	MagnaTrack Horizontal 17,7m (59')	160		20804664*
	MagnaTrack Horizontal 7,0m (23')	160		20806864*
	MagnaTrack extraction unit ø 130 mm, 3m vertical	130	3	20801564**
	MagnaTrack extraction unit ø 130 mm, 4m vertical	130	4	20801664**
	MagnaTrack extraction unit ø 160 mm, 3m vertical	160	3	20801764**
	MagnaTrack extraction unit ø 160 mm, 4m vertical	160	4	20801864**
	Complete extraction unit, Ø160 for high level (HL) exhaust pipes	160	2	20801964


\*Including - Guide Track (1), Mounting brackets for 2.4 m distance (2), Shock absorber (3), Horizontal hose (4), Transformer (12)

\*\*Including - Trolley (5), Balancer (6), Vertical hose (7), Electro-magnet assembly (9), Anchor plate (10), Disconnection box (11)

## Magna Track HS



Toebehoren		Artikelnummer
	Magna System Nozzle Standard, Ø160, Low Level	20802164
	Magna System Nozzle Ø160 (6'') HB 600 Low Level	20802264
	MagnaSystem Nozzle Ø130 (5'') HB 600 Low Level	20802364
	Magna System Nozzle Ø160 (6'') HB 900 Low Level	20802464
	Scoop Nozzle HB 600 Low Level 5''	20814263
	Scoop Nozzle HB 600 6'' Low Level	20814463
	Radio transmitter vehicle GHz	20376723
	Radio Receiver GHz	20376724
	Handheld radio transmitter GHz	20376725
	Program kit for radio system	20376726
	Slang beschermingshoes Ø 130/160 mm (set)	20374428
	Anchor plate, shutter, in 3 parts	20371868
	Twist support, HL nozzle	20374364
	Lengthening shaft, HL nozzle	20374359

## Magna Track HS



y1: Pa, x1: m<sup>3</sup>/h, x2: CFM y2: W.C



## Magna Track HS



Length of rail, m	No. of brackets
3.5	2
5.9	3
7	4
9.5	4
11.8	5
15.3	7
17.7	9

N.B. The nozzle for high level (HL) exhaust pipes must be installed at a higher level than the exhaust pipe. The nozzle must be pulled downwards at connection, which will activate the balancer.

## Magna Track HS



Length of rail, m / ft	No. of brackets
5.9 / 19.4	3
7 / 22.9	4
9.5 / 31.2	4
11.8 / 38.7	5