

平衡臂

符合人体工程学，节省空间，死角处也能充分吸除



为了尽量彻底清洁每个角落，平衡抽排臂内置有两个用烟气挡板保持稳定的部分。吸尘器有三个旋转点，一个在底部，一个在中间，一个在喷嘴连接处。因此可将喷嘴移至平衡臂可及范围内的任何位置。平衡臂可配备尼的曼高真空吸尘器计划范围内的所有吸嘴。侧向移动的摩擦是可调的。平衡臂有三种不同的安装方式:安装至墙上、工作台或延伸臂。

安装支架、喷嘴(CWN-S或FVN)、手柄和软管(FS或WH软管)须单独订购。安装支架、喷嘴、手柄和软管须单独订购。

经济、安全
平衡性佳、灵活
易操作
通用性佳

品名	平衡臂
----	-----

平衡臂

臂长 (米)	重量 (公斤)	产品编号
1,5	9,7	40180000
2,5	16,5	40180010
3,5	19,2	40180020

平衡臂

附件		产品编号
	工作台支架, BA	40180040
	墙面安装支架, BA	40180030
	墙面安装支架, BA 500mm	40180070
	Hose WH-38 L=10m m.spiral	40160292
	Hose WH-51 L=10m m.spiral	40160272
	EA250 延伸臂 (2.5m)	40180050
	EA450 延伸臂 (4.5m)	40180060
	Nozzle FWN 200/50, connection D=50 mm, airflow 250 m3/h, width 200 mm	40290110*
	Nozzle FWN 400/50, connection D=50 mm, airflow 250 m3/h, width 400 mm	40290120*
	CWN-S 105/50 nozzle silencer, connection D=50 mm, airflow 250 m3/h, suction diameter 105 mm	40290230**
	CWN-S 105/63 nozzle silencer, connection D=63 mm, airflow 400 m3/h suction diameter 105 mm	40290240**
	Nozzle CWN-S 105/50L silencer, connection D=50 mm, airflow 250 m3/h	40290270***
	Nozzle CWN-S 105/40, connection D=40 mm,, airflow 200 m3/h	40290330**
	SOV 50, Manual shut off valve (D=50)	40140030
	SOV 40, Manual shut off valve (D=40)	40142510
	喷嘴延伸	40290200

*Fish tail nozzle. For mounting on balance arms, magnet or suction base. Must be combined with nozzle extension when used with balance arms.

**Noise reducing nozzle. For mounting on balance arms, magnet or suction base.

***Noise reducing nozzle with flexible steel tube extension. For mounting on balance arms, magnet or suction base.