

## Industrial vacuum cleaner 426 A


Vacuum for extraction of dry waste and powders



Industrial dry vacuum cleaner 426A is designed for removal and collection of industrial waste and spillage. This powerful dry vacuum suction unit comes equipped with a silo and cyclonic pre-separator before the filter, ensuring efficient collection of large quantities of material. The 426A Industrial vacuum can also be equipped with a HEPA filter for finer particles. The industrial vacuum cleaner includes slots for handling by forklift. Special swiveling, locking wheels are sized to increase mobility, and make the handling of heavy loads especially easy. The dry vacuum's cyclonic silo is equipped with a manual valve





- Pre-separation in silo
- Manual filter cleaning prolongs the filter's lifetime
- Forklift handling

Product name	Industrial vacuum cleaner 426 A
Installation	Outdoor, Indoor
Filter cleaning method	Reverse air pulse
Application	Dust, Granulate, Grit, Chip
Dustbin volume (gal)	58 l cyclonic silo + 47 l dust bin
Hose length (ft.)	24.6 ft
Filter Area (ft <sup>2</sup> )	17
Filter type	Cartridge
Number of filter elements	1
Filter material	Microfibre
Weight (lbs)	262
Hose length (m)	25
Hose diameter (mm)	2
Note	Manual discharge valve



Granulate Grit Chip Dust

## Industrial vacuum cleaner 426 A






Image	Description	Type of hose <sup>1</sup>	Compressed air requirement	Max airflow (m <sup>3</sup> /h)	Noise level (dB(A))	Max vacuum (in. wg)	Model
	426A - NE42, Extended height. With floor cleaning equipment, scraping tool and conical nozzle	PVC	2,2 Nm <sup>3</sup> /min	360	73.5	-169	42142602*
	426A - NE52, With floor cleaning equipment, scraping tool and conical nozzle	PVC	3,0 Nm <sup>3</sup> /min	342	75.5	-209	42142600*
	426A - NE52, With floor cleaning equipment	PVC	3,0 Nm <sup>3</sup> /min	342	75.5	-209	42142606*
	426A - NE74, With floor cleaning equipment, scraping tool and conical nozzle	PE/C	5,3 Nm <sup>3</sup> /min	318	75.0	-313	42142601*

\*Manual discharge valve


<sup>1</sup> See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PVC	Max vacuum 84 kPa Inner bending radius 6 cm Reinforced with imbedded steel helix	- 20 deg. C. to + 70 Deg. C.				
PEC	For cleaning applications Max vacuum 50 kPa Conductivity < 10 <sup>-6</sup> Ohm	-40 Deg. C. - +60 Deg. C.				

# Industrial vacuum cleaner 426 A

Accessory		Part No
	Control S for NE 22-76	43220001
	Control S for NE 22-76	43220026
	Control S for NE86-96	43222008
	Plastic bag S50 - 25pcs 500 x 600 mm with hole for bin balancing	43650102
	Plastic bag S50 - 25pcs 630x800 mm with hole for bin balancing	43650103

## Industrial vacuum cleaner 426 A



Air Powered ejectors

All performance data are based on 7 bar supply pressure