

450A

dust collectors with NCF filter




Single container system for fixed installation. Equipped with NCF filter which is automatically cleaned at each system stop. Cyclonic discharge of the material into a container of 47 liters (12 gal). Powerful vacuum unit suitable for recovery of dust, grit and granulated material. The unit is efficient for collecting greasy chips from lathes and drilling machines in a central suction system.

- Efficient vacuum unit requiring minimal floor space
- Efficient self-cleaning NCF filter
- High suction capacity

Product name	450A
Installation	ในอาคาร
Filter cleaning method	เป่าอากาศแบบไหลย้อน
Application	ฝุ่น, เมล็ด, กรวด, เศษ
Dustbin volume (l)	47
Filter Area (m2)	1,6
Type of hose	-
Weight (kg)	88




450A

รูปภาพ	Description	Filter type	Number of filter elements	Filter material	Compressed air requirement	Max airflow (m ³ /h)	Noise level (dB(A))	Max vaccum (kPa)	รุ่น
	450A - NE66 without frame, orange	ไส้กรองแบบตลับ	1	Microfibre	4,1 Nm ³ /min	630	76.5	-38	42145010
	450A - NE42, with 1" quick coupling without accessories	ไส้กรองแบบถลุง	70	Vyon	2,2 Nm ³ /min	360	73.5	-42	42145018

450A

Air powered ejectors pressure / flow diagram



Air Powered ejectors

All performance data are based on 7 bar supply pressure