

710A

Dust collector with pre-separator for grit recovery



This robust and extremely powerful system is designed for the recovery of blasting shot. Equipped with automatic pneumatic pinch valve and automatic self-cleaning NCF filter. Most of the dust is separated from the blasting shot or from the collected granulates. The dust is channelled into its own container, while the blasting shot or granulated material is fed back into the blasting pot, onto conveyors or into other containers.

- Extremely high vacuum for suction of heavy material over long horizontal and vertical distances-
- Dust separation from collected granules and grit
- Automatic filter cleaning and silo discharge


Product name	710A
Installation	ในอาคาร
Filter cleaning method	เป่าอากาศแบบไหลย้อน
Application	กรวด, เมล็ด
Dustbin volume (l)	67 + 220
Hose length (m)	10
Filter Area (m2)	3,15
Number of filter elements	70
Filter material	NCF 3,15
Type of hose	PU12
Compressed air requirement	5,3 Nm3/min
Max airflow (m3/h)	318
Noise level ((dB)A)	75.0
Max vaccum (kPa)	-78
Weight (kg)	271
Hose length (m)	10
Hose diameter (mm)	63



เมล็ด


กรวด

710A


รูปภาพ	Description	รุ่น
	710A - NE74, S200.	42171000

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PU12	เหมาะสำหรับวัสดุที่มีฤทธิ์กัดกร่อนยูรีเทนใส่เสริมด้วยเหล็กเกลียวฝังตัว	- 40 deg. C. + 90 Deg. C.				

710A



Air powered ejectors pressure / flow diagram



Air Powered ejectors

All performance data are based on 7 bar supply pressure