

Drum filler 014A



Handy ejector-driven drum filler for collection and transport of oil, chemicals, water and other liquids. It is placed in a bung-hole (R 2") of an empty but suitable oil drum. By connecting the unit to a compressed air hose and a suction hose, it is ready for use. Suction stops when the drum is full, due to the built-in float stop. The ejector is easy to mount on a variety of drums. Drum is not included.

- Simple and robust ejector
- No filter is needed
- Drum is not included
- Easy handling

Product name	Drum filler 014A
Noise level (dB(A))	80
Compressed air requirement	7 bar
Compressed air consumption	0,7 Nm ³ /min
Installation	[Indoor]
Material	Hose in conductive PE
Application	[liquid]
Hose length (m)	5
Type of hose	[PE]
Compressed air requirement	0,7 Nm ³ /min
Max airflow (m ³ /h)	132
Noise level (dB(A))	80.0
Max vacuum (kPa)	-23
Weight (kg)	8
Hose length (m)	5
Hose diameter (mm)	38



Liquid

Drum filler 014A

[image]	Description	[model]
	014A NE14	42101402*
	014A NE14	42101404**

*With cleaning set and conical nozzle and trolley

**With cleaning set

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PE		-40 Deg. C - +60 deg. C.				

Drum filler 014A

