

Pneumatic oil pumps

Pneumatic pumps for grease, oil and other liquids



Ideal oil pumps for transferring low-viscosity fluids such as motor oil, old waste oil, antifreeze, transmission oil, ATF oil and other similar products. The pumps can be wall-mounted or placed directly on the drum/tank. With the aid of special accessories, many application areas can be supported.


| | |
|--------------|---------------------|
| Product name | Pneumatic oil pumps |
|--------------|---------------------|



Pneumatic oil pumps

| Image | Description | Max working pressure (Mpa) | Inlet | Capacity | Inlet Media | Model |
|---|--|----------------------------|------------------|-----------------------|-------------------|-----------|
|  | Oilpump 3:1 for medium to heavy applications. Includes wallbracket and bung adaptor. Suction tube 180 mm long. | 1 | ISO-G1/4" Female | 20 l/min | ISO-G1" Male | 30580750 |
|  | Oilpump 3:1 for medium to heavy applications. Includes wallbracket and bung adaptor. Suction tube 910 mm long. | 1 | ISO-G1/4" Female | 20 l/min | ISO-G1" Male | 30580850 |
|  | Oilpump 3:1 for lighter applications. With bung adaptor. Suction tube 940 mm long. | 0,8 | 1/4" BSP Female | 13 l/min | 1" LP adapter | 30599250 |
|  | Oilpump 5:1 for lighter applications. With bung adaptor. Suction tube 940 mm long. | 0,8 | 1/4" BSP Female | 14 l/min | 1" LP adapter | 30599450 |
|  | Oil Pump 5:1., High Flow for medium to heavy applications, Pump tube Ø56mm, tube length 270 mm with wall bracket | 1,2 | 3/8" BSP Female | 40 l/min | 1 1/2" BSP Female | 30599550* |
|  | Oilpump 3:1 for lighter applications. Includes wallbracket and Ø42 mm pump tube and bung adaptor Suction tube 270 mm long. | 0,8 | 1/4" BSP Female | 12 l/min | 1" LP adapter | 30599150 |
|  | Oilpump 5:1 for lighter applications. With bung adaptor. Suction tube 270 mm long. | 0,8 | 1/4" BSP Female | 14 l/min | 1" LP adapter | 30599350 |
|  | Oil Pump 6:1., High Flow for medium to heavy applications, Pump tube Ø50 mm, tube length 960 mm | 1 | 1/4" BSP Female | 23 l/min | 3/4" BSP Female | 39100022 |
|  | Grease pump 65:1 for lighter applications. Pump tube Ø30 mm, tube length 740 mm. For 60 kg drums. | 0,8 | 3/4" BSP Female | 1000 gr/min at 6 bar | | 30599650 |
|  | Grease pump 65:1 for lighter applications. Pump tube Ø30 mm, tube length 940 mm. For 180 kg drums. | 0,8 | 3/4" BSP Female | 1000 gr/min at 6 bar | | 30599750 |
|  | Waste oil pump. Max Vacuum -95 kPa | 1 | 1/4" BSP Female | 23 l/min | 1" BSP Female | 30508950 |
|  | Diaphragm pump 1:1 | 0,8 | 1/4" BSP Female | 60 l/min | 3/4" BSP Female | 30507950 |
|  | Diaphragm pump 1:1 | 0,8 | 1/4" BSP Female | 100 l/min | 1" BSP Female | 30600050 |
|  | Kit grease pump 65:1 "Well empty" for 1/1 drum | 1 | 1/4" BSP Female | 1200 gr/min at 10 bar | | 30509050 |
|  | Kit grease pump 65:1 "Well empty" for 1/4 drum | 1 | 1/4" BSP Female | 1200 gr/min at 10 bar | | 30509850 |























Pneumatic oil pumps

| Image | Description | Max working pressure (Mpa) | Inlet | Capacity | Inlet Media | Model |
|---|--|----------------------------|------------------|---------------------|-------------|------------|
|  | Pneumatic piston pump 3:1 for low/medium viscosity fluids such as anti freeze windscreen liquid and chemical liquids without tensides. Tube length 940 mm. | 1 | ISO-G1/4" Female | 23 l/min | | 30581850** |
| | Pneumatic piston pump for wall installation 3:1 for low/medium viscosity fluids such as anti freeze windscreen liquid and chemical liquids without tensides. Tube length 940 mm. Hose length 1 600 mm. | 1 | ISO-G1/4" Female | 24 l/min | | 30581950 |
| | Grease pump 50:1 for lighter applications. Pump tube Ø30 mm, tube length 740 mm. For 20-30 kg drums. | 0,8 | 1/4" BSP Female | 800 gr/min at 6 bar | | 30583050 |
| | Grease pump 50:1 for lighter applications. Pump tube Ø30 mm, tube length 480 mm. For 50-60 kg drums. | 0,8 | 1/4" BSP Female | 801 gr/min at 6 bar | | 30583150 |





*Air consumption - 600l/min (0,8MPa)

**Min air pressure 0,3 bar

Pneumatic oil pumps

| | Accessory | Part No |
|--|-----------------------------|----------|
|  | Air Management kit | 30512150 |
|  | Hosekit 1,8m, complete | 30511950 |
|  | Hosekit 4m, complete | 30500550 |
|  | Hosekit 1" | 30511850 |
|  | Suction kit HP 940mm | 30580950 |
|  | Suction kit LP 940mm | 30581150 |
|  | Drum adaptor 42mm | 30501150 |
|  | Top connection | 30580650 |
|  | Extension tube 500mm | 30580450 |
|  | Extension tube 200mm | 30580550 |
|  | Extension sleeve | 30580350 |
|  | Foot connection | 30580250 |
|  | Foot valve | 30580150 |
|  | Filter | 30599950 |
|  | Suctionkit 3/4" | 30581650 |
|  | Wall Suctionkit with probes | 30581750 |
|  | Complete 1 1/4" filter | 30594550 |
|  | DRUM COVER Ø 350 mm 20kg | 30503550 |
|  | DRUM COVER Ø 420 mm 50kg | 30503650 |
|  | DRUM COVER Ø 600 mm 180kg | 30503750 |
|  | Drum cover 310mm | 30593450 |
|  | FOLLOWER PLATE Ø 340 | 30503850 |

Pneumatic oil pumps

| Accessory | | Part No |
|---|------------------------|----------|
|  | FOLLOWER PLATE Ø 410 | 30503950 |
|  | Follower plate Ø 585 | 30504050 |
|  | Follower plate 310mm | 30593550 |
|  | Ball valve 3/8" grease | 30592250 |