

用于润滑油、油和其他液体的气动泵



为输送低粘度液体如机油、旧废油、防冻剂、传动油、ATF油和其他 类似液体的理想油泵。泵可以安装至墙壁或直接置于桶/罐。借助专用 配件可以支持许多应用领域。

品名

气动抽油泵

 ϵ



[image]	产品名称	最大工作压力(Mpa)	Inlet	Capacity	Inlet Media	产品编号
	Oilpump 3:1 for medium to heavy applications. Includes wallbracket and bung adaptor. Suction tube 180 mm long.	1	ISO-G1/4" Female	20 l/min	ISO-G1" Male	30580750
\$	Oilpump 3:1 for medium to heavy applications. Includes wallbracket and bung adaptor. Suction tube 910 mm long.	1	ISO-G1/4" Female	20 l/min	ISO-G1" Male	30580850
***	Oilpump 3:1 for lighter applications. With bung adaptor. Suction tube 940 mm long.	0,8	1/4" BSP Female	13 l/min	1" LP adapter	30599250
	Oilpump 5:1 for lighter applications. With bung adaptor. Suction tube 940 mm long.	0,8	1/4" BSP Female	14 l/min	1" LP adapter	30599450
#	Oil Pump 5:1., High Flow for medium to heavy applications, Pump tube 56mm, tube length 270 mm with wall bracket	1,2	3/8" BSP Female	40 l/min	11/2" BSP Female	30599550*
	Oilpump 3:1 for lighter applications. Includes wallbracket and 42 mm pump tube and bung adaptor Suction tube 270 mm long.	0,8	1/4" BSP Female	12 l/min	1" LP adapter	30599150
#	机油油泵 6:1.,高流量 ,适合中型至重型应用车 ,泵管管径 50 mm,管 长 160 mm,带墙壁支 架	1	1/4" BSP Female	1/4" BSP Female	3/4" BSP Female	39100005
4	机油油泵 6:1.,高流量 ,适合中型至重型应用车 ,泵管管径 50 mm,管 长 960 mm	1	1/4" BSP Female	1/4" BSP Female	3/4" BSP Female	39100022
	Grease pump 65:1 for lighter applications. Pump tube 30 mm, tube length 740 mm. For 60 kg drums.	0,8	3/4" BSP Female	1000 gr/min at 6 bar		30599650
	Grease pump 65:1 for lighter applications. Pump tube 30 mm, tube length 940 mm. For 180 kg drums.	0,8	3/4" BSP Female	1000 gr/min at 6 bar		30599750
1	废油泵。最大真空负压 - 95 kPa	1	1/4" BSP Female	1/4" BSP Female	1" BSP Female	30508950
	膜片泵 1:1	0,8	1/4" BSP Female	1/4" BSP Female	3/4" BSP Female	30507950
	套件油脂泵 65:1 "空井" 1/1 圆筒	1	1/4" BSP Female	1/4" BSP Female		30509050
	套件油脂泵 65:1 "空井" 1/4 圆筒	1	1/4" BSP Female	1/4" BSP Female		30509850
	Pneumatic piston pump 3:1 for low/medium viscosity fluids such as anti freeze windscreen liquid and chemical liquids witout tensides. Tube length 940 mm.	1	ISO-G1/4" Female	23 l/min		30581850**



[image]	产品名称	最大工作压力(Mpa)	Inlet	Capacity	Inlet Media	产品编号
	Pneumatic piston pump for wall installation 3:1 for low/medium viscosity fluids such as anti freeze windscreen liquid and chemical liquids witout tensides. Tube length 940 mm. Hose length 1600 mm.	1	ISO-G1/4" Female	24 l/min		30581950

^{*}Air consumption – 600l/min (0.8MPa) **Min air pressure 0,3 bar



	附件	产品编号
*	空气管理套件	30512150
	软管套件 1.8米	30511950
	软管套件 4米	30500550
	废油软管套件 长940mm	30580950
	Suction kit LP 940mm	30581150
	圆筒接头 42mm	30501150
	Top connection	30580650
	Extension tube 500mm	30580450
	Extension tube 200mm	30580550
	Extension sleeve	30580350
	Foot connection	30580250
	Foot valve	30580150
	Filter	30599950
	Suctionkit 3/4"	30581650
Ť	1 1/4"BSP 螺纹 过滤器	30594550
	圆筒罩 直径600mm 180KG	30503750
	从动板 直径585mm	30504050