

Høyvakuumsventiler, TAV 100/150

Manuelle og automatiske ventiler maksimerer effektiviteten av høyvakuumsystemet.



TAV 100- og TAV 150-ventilene brukes hovedsakelig som flaskeventiler i de viktigste grenene av rør. Fordi ventilene kan åpnes og lukkes automatisk, er vakuuet alltid konsentrert på tilkoblinger, utsugspunkter eller maskiner i drift samtidig. Dette maksimerer kraften i utsuget og gir lavere driftskostnader og reduserer størrelsen på vakuumenheten.






Produktnavn	Høyvakuumsventiler, TAV 100/150
Installasjon	Innendørs
Max vakuum (kPa)	50
Max pressure (kPa)	1000
Operating temperature range	0° to +40°C (32 F to 104 F)
Max vaccum (kPa)	



Høyvakuumsventiler, TAV 100/150

Navn på datablad	Diameter (mm)	Model
TAV 100 MA	100	40146010
TAV1002PC	100	40146030
TAV 150 MA	150	40146040
TAV 150 PC EX	150	40146060
TAV 100 MV 230V AC EX	100	40146080
TAV 100 MV 24V DC EX	100	40146082
TAV 100 MV 115V AC EX	100	40146083
TAV 150 MV 230V AC EX	150	40146100
TAV 150 MV 24V AC/DC	150	40146101
TAV 150 MV 24V DC EX	150	40146102
TAV 150 MV 115V AC EX	150	40146103

Høyvakuumsventiler, TAV 100/150

Tilbehør		Artikkelnummer
	Pressure pilot switch for automatic start/stop with TAV 100 and TAV 150.	40141780
	5/2-port pneumatic control valve (rocker) for control of double-action cylinder. Suitable for TAV 100 and TAV 150. Set includes couplings and hose (6/4 mm, 25 m).	40680250
	Hose (25m), PVC, for compressed air	40650021
	Wire Connector 2,5 mm ² , 1-pole.	40730170
	Pilotkabel 2x0,75mm ² PVC L=100 m	40730403
	Pilotkabel 3x0,75mm ² PVC L=100 m	40730404
	Electric time delay box	40780331