

高真空阀TAV 100/150

手动和自动阀可使高真空系统的效率最大化。



TAV 100和TAV 150阀主要用作管道系统的主要分支的关闭阀。由于阀门可以自动开启和关闭，真空始终集中于连接处、抽排点或正在运行中的机器。这样可以将抽排力最大化，降低运营成本，减少真空装置的大小。






品名	高真空阀TAV 100/150
安装	室内
最大负压 (千帕)	50
Max pressure (kPa)	1000
作业温度	0° to +40° C (32 F to 104 F)
Max vaccum (kPa)	



高真空阀TAV 100/150

产品名称	直径 (mm)	产品编号
TAV 100 MA	100	40146010
TAV1002PC	100	40146030
TAV 150 MA	150	40146040
TAV 150 PC EX	150	40146060
TAV 100 MV 230V AC EX	100	40146080
TAV 100 MV 24V DC EX	100	40146082
TAV 100 MV 115V AC EX	100	40146083
TAV 150 MV 230V AC EX	150	40146100
TAV 150 MV 24V AC/DC	150	40146101
TAV 150 MV 24V DC EX	150	40146102
TAV 150 MV 115V AC EX	150	40146103

高真空阀TAV 100/150

附件		产品编号
	Pressure pilot switch for automatic start/stop with TAV 100 and TAV 150.	40141780
	5/2-port pneumatic control valve (rocker) for control of double-action cylinder. Suitable for TAV 100 and TAV 150. Set includes couplings and hose (6/4 mm, 25 m).	40680250
	Hose (25m), PVC, for compressed air	40650021
	Wire Connector 2,5 mm ² , 1-pole.	40730170
	远程信号线, 2x0.75mm ² , PVC, 长100m	40730403
	信号线,3股0.75平方, PVC, 100m长	40730404
	Electric time delay box	40780331