

425A

Industrial vacuum cleaner for removal of industrial waste



Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container fitted with our exclusive nederman vyon self-cleaning filter ensuring the efficient filtration of large quantities of dust. The filter is cleaned automatically when the air supply is turned off. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads especially simple. The unit is equipped with an adjustable counterweight valve and sack holder for discharge into sacks. The model include slots for handling by forklift.

- Dry waste suction
- Silo pre-separator with manual outlet valve
- Fork lift handling
- Sturdy trolley system with large wheels for uneven ground
- automatic filtercleaning

Produkt namn	425A
Typ av filter	Patron
Antal filter	1
Slangtyp	PVC
Tryckluftsbehov	3,0 Nm ³ /min
Max luftflöde (m ³ /h)	342
Ljudnivå (dB(A))	75,5
Max vaccum (kPa)	-52
Vikt (kg)	119
Slanglängd (m)	7,5
Slangdimension (mm)	51
Observera	






425A

Beskrivning	Model
425A - NE52	42142500

Slangtyp	Specifikation	Temperatur område, °C	Slangkoppling, fri ände distributionsslang	Slangkoppling, fri ände anslutningsslang	Slanganslutning på upprullare, distributionsslang	Slangkoppling på upprullare, anslutningsslang
PVC	Max vacuum 84 kPA Inre krökningsradie 60 mm Förstärkt med helinbäddad stålspiral	- 20 deg. C. to + 70 Deg. C.				

425A

Tillbehör		Artikelnummer
	Kontrollsystem för NE86-96	43222008
	Kontrollsystem för NE 22-76	43220026
	Kontrollsystem för NE 22-76	43220001

425A



Air Powered ejectors

All performance data are based on 7 bar supply pressure