

## 高负压吸嘴

---









尼的曼焊接吸嘴可以与平衡臂很好的配合使用，但也可以提供磁性底座，参阅一下配件，CWN吸嘴经过消音，以实现最佳的操作舒适性。

---

专为高真空吸尘器而设计，不降低性能

品名	高负压吸嘴
----	-------

## 高负压吸嘴

[image]	产品名称	产品编号
	Nozzle FWN 200/50, connection D=50 mm, airflow 250 m <sup>3</sup> /h, width 200 mm	40290110*
	Nozzle FWN 400/50, connection D=50 mm, airflow 250 m <sup>3</sup> /h, width 400 mm	40290120*
	Nozzle CWN-S 105/40, connection D=40 mm, airflow 200 m <sup>3</sup> /h	40290330**
	CWN-S 105/50 nozzle silencer, connection D=50 mm, airflow 250 m <sup>3</sup> /h, suction diameter 105 mm	40290230**
	CWN-S 105/63 nozzle silencer, connection D=63 mm, airflow 400 m <sup>3</sup> /h suction diameter 105 mm	40290240**
	Nozzle CWN-S 105/50L silencer, connection D=50 mm, airflow 250 m <sup>3</sup> /h	40290270***

\*Fish tail nozzle. For mounting on balance arms, magnet or suction base. Must be combined with nozzle extension when used with balance arms.

\*\*Noise reducing nozzle. For mounting on balance arms, magnet or suction base.

\*\*\*Noise reducing nozzle with flexible steel tube extension. For mounting on balance arms, magnet or suction base.

## 高负压吸嘴

附件		产品编号
	磁座	40290170
	尾气抽排底座	40290180
	吸嘴延伸	40290200
	传感器	40750020
	手柄, CWN-S 105/50 & 63	40070420