

## Industrial vacuum cleaner 115 E

## Industrial dry vacuum cleaner for workshop cleaning



Electric powered industrial vacuum cleaner with a single container system, designed for the collection of dry or wet materials over short distances. Versatile vacuum for use in diverse industries and institutions. The vacuum suction equipment is light and easy to handle.

- Versatile extractor
- Perfect for workshops

Product name	Industrial vacuum cleaner 115 E
Noise level (dB(A))	75
Installation	Indoor
Filter cleaning method	One way filter
Application	Dust, Liquid, Granulate, Swarf
Dustbin volume (I)	40
Max Airflow (m3/h)	460
Filter Area (m²)	0.35
Frequency (Hz)	50/60
No of phases	1
Filter type	Bag
Number of filter elements	1
Filter material	Polyester-Teflon
Max airflow (m³/h)	460
Noise level (dB(A))	75
Max vaccum (kPa)	-21,5
Weight (kg)	50
Power (kW)	2,4











Granulate

Swarf

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB www.nederman.com



## Industrial vacuum cleaner 115 E

lmage	Description	Power Voltage (V)	Type of hose <sup>1</sup>	Hose length (m)	Hose diameter (mm)	Model
	115E - NEL3	110	PE/C	7,5	51	42411582*
	115E - NEL3R	230	PE/C	7,5	51	42411581*
	115E - NEL3	110	PVC	7,5	51	42411501**
	115E - NEL3R	230	PE/C	5	38	42411580

<sup>&</sup>lt;sup>1</sup> See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
	For cleaning applications					
PEC	Max vacuum 50 kPa	-40 Deg. C +60 Deg. C.				
	Conductivity 10^3 to 10^6 Ohm/m					
PVC	Max vacuum 84 kPA					
	Inner bending radius 60 mm	- 20 deg. C. to + 70 Deg. C.				
	Reinforced with inbedded steel helix					

<sup>\*</sup>With cleaning set \*\*With cleaning set, toothed and conical nozzle