

Cartridge filter for both indoor and outdoor installations. The filter can be used for many different dust producing industries.





MCP SmartFilter is a multi-purpose filtration system. It is customizable to perfectly fit customer specific demands with airflow up to 28,000 m3/h. Suitable for smoke, fumes and dust and can be used in several different applications such as welding, metal cutting and general dust.

The modular design allows for standalone solutions as well as multifilter solutions for extended requirements. With a new and innovative cartridge design - the squircle shape utilizes the square space within the dust collector in the most optimal way and generates high cartridge airflow. Thus, decreasing the size and hence the footprint of the system.

Constructed with 2 mm galvanized steel panels, it is easy to install, cost effective to ship and provides corrosion protection. The design is optimized for long filter lifetime providing low cost of ownership. Insight ready control with advanced pulse cleaning logic provides for full system operation including control and monitoring, as well as gateway functionality for cloud communication.

The MCP SmartFilter has a large accessories program including; fans, inlets, bins etc. and the cartridges are available in a wide variety of materials.

- Gain control over filtration performance with Insight Analytics. Nederman's unique monitoring technology.
- Optimized footprint through innovative cartridge design with high airflow.
- Reduced TCO through intelligent cleaning system, long filter cartridge life-time and optimized footprint.
- Future Proof system that is IoT prepared- Insight Ready.
- Controller, HMI and Gateway all in one unit with the Insight Control Panel.

Medya	MCP SmartFilter	
Kompresor hava tüketimi	60 litres per cleaning pulse at 6,0 bar compressed air	
Kurulum	[Indoor], [Outdoor]	
Materyal	2 mm galvanised sheet metal	
Patlayıcı toz için ideal	False	
Filtre temizlik metodu	[PulseJet]	
Application	[fumes], [dust]	
Çalışma Basınçı (kPa)	Vacuum max. 6 kPa. Overpressure max. 0 Pa. (1,5 kPa for silotop solution)	
Çöp kovası (I)	50 or 100 litre bin	
Filitre alanı (m²)	Polyester: 30 to 192 m2 SC178: 67 to 422 m2 SC179: 32 to 208 m2	
Kapasite(maks. Hava debisi m3/h)	4500 to 28000	
Operating Temperature	-20 to +70 Deg. C.	
Filtre türü	[cartridge]	
Filtre materyali	Uygulamaya bağlı olarak	



Renk
Teknik bilgi onayı
Konfigüre edilmiş ürün









[image]	Bilgi Dökümanı ismi	Filtre adedi	[model]
AA	MCP-2-8S Akıllı filtre	8	MCP-2-8S*
	MCP-4-16S Akıllı filtre	16	MCP-4-165*
	MCP-6-24S Akıllı filtre	24	MCP-6-24S*
	MCP-8-32S Akıllı filtre	32	MCP-8-32S*
	MCP-2-8SL Akıllı filtre	8	MCP-2-8SL*
	MCP-4-16SL Akıllı filtre	16	MCP-4-16SL*
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	MCP-6-24SL Akıllı filtre	24	MCP-6-24SL*
	MCP-8-32SL Akıllı filtre	32	MCP-8-32SL*

^{*}Konfigüre edilmiş ürün



Cartridge material

- SC100 Spunbond polyester
- SC140 Spunbond polyester with antistatic treatment
- SC141 Spunbond polyester with antistatic treatment and PTFE coating
- SC150 Spunbond polyester with ePTFE membrane
- SC151 Spunbond polyester with antistatic treatment and ePTFE membrane
- SC178/SC179 80% cellulose, 20% polyester material with nanofiber
- SC190 Spunbond polyester with PTFE coating

A – Height of Clean Air Chamber (mm)			
200	350	500	650
Shown in drawings	Add 150 mm in height	Add 300 mm in height	Add 450 mm in height

Filter area

Filter type	Quantity of	uantity of Filter area (m²)			Max. airflow (m³/h)*
Filter type	cartridges	SC100, SC140, SC141, SC150, SC151, SC190	SC178	SC179	wax. airiiow (m-/ii)
MCP-2-8S MCP-2-8S-Ex	8	48,0	105,6	52,0	7000
MCP-4-16S MCP-4-16S-Ex	16	96,0	211,2	104,0	14000
MCP-6-24S MCP-6-24S-Ex	24	144,0	316,8	156,0	21000
MCP-8-32S MCP-8-32S-Ex	32	192,0	422,4	208,0	28000
MCP-2-8SL MCP-2-8SL-Ex	8	30,4	67,2	32,8	4500
MCP-4-16SL MCP-4-16SL-Ex	16	60,8	134,4	65,6	9000
MCP-6-24SL MCP-6-24SL-Ex	24	91,2	201,6	98,4	13500
MCP-8-32SL MCP-8-32SL-Ex	32	121,6	268,8	131,2	18000


*Max. air flow is dependent on the dust type, etc



Figure	Description	Figure	Description
	Top mounted FM-fans 50 Hz or 60 Hz up to 14000 m³/h		Leg height extensions from 0 mm to 2000 mm to fit larger bins/containers, rotary valves and big bags
	Combifab remote fans 50 Hz or 60 Hz		Leg width extension 300 mm to left, right or both sides to fit larger bins/containers, rotary valves and big bags
	Noise enclosure to reduce fan and motor break-out- noise of FM-fans	T	Suspension below rotary valve for big bag
	Dual silencer to reduce air flow, fan noise and motor break-out-noise of FM-fans (available with grid (indoor use), grid and rain cover (outdoor use) or flange for duct connection)		Isolation box for pressure tank incl. cleaning valves
	Regulation (iris) damper at fan inlet for FM-fans		Access platform with ladde for maintenance
eel	Dust bins (50 I, 50 I with wheels and 100 I with wheels)		Lime feeder NFKG-70
	Plastic bag in the dust bin with pressure compensation set 'bin balancing'	0 🛊 🔪	Several sensors available for extraction, filtration and discharge process
	Rotary valves NRS3 and NRSZ3		Water separator and pressure regulator
	Dust discharge valve NFUS3		QF-duct system



MCP-2-8S / MCP-2-8S-Ex MCP-2-8SL / MCP-2-8SL-Ex





All dimensions in mm.

^{*} to be included only if a top mounted FM fan is used (transition for fan).



MCP-4-16S / MCP-4-16S-Ex MCP-4-16SL / MCP-4-16SL-Ex






All dimensions in mm.

^{*} to be included only if a top mounted FM fan is used (transition for fan).



MCP-6-24S / MCP-6-24S-Ex MCP-6-24SL / MCP-6-24SL-Ex




All dimensions in mm.

^{*} to be included only if a top mounted FM fan is used (transition for fan).



MCP-8-32S / MCP-8-32S-Ex MCP-8-32SL / MCP-8-32SL-Ex



All dimensions in mm.

^{*} to be included only if a top mounted FM fan is used (transition for fan).