

## Sugeslange PE/C

---



Bruksområder: Lett og fleksibel avsugsslange. Hovedsakelig egnet for rengjøring hvor eksepsjonell ledningsevne for statisk elektrisitet kreves.



- Glatt boreledende slange.
- Maks. vakuum 50 kPa.
- Temp.område: -40 °C til +60 °C.
- Ledningsevne <  $10^6 \Omega/m$

Produktnavn	Sugeslange PE/C
Max vakuum (kPa)	50
Max vaccum (kPa)	50

# Sugeslange PE/C

Bilde	Navn på datablad	Diameter (mm)	Length (m)	Model
	Slange PE/C Ø 25 L=15m	25	15	40160305
	Slange PE/C Ø 32 L=5m	32	5	40160311
	Slange PE/C Ø 32 L=10 m	32	10	40160313
	Slange PE/C Ø 32 L=15m	32	15	40160315
	Slange PE/C Ø 38 L=5m	38	5	40160321
	Slange PE/C Ø 38 L=10 m	38	10	40160322
	Slange PE/C Ø 38 L=15m	38	15	40160323
	Slange PE/C Ø 51 L=5m	51	5	40160331
	Slange PE/C Ø 51 L=15m	51	15	40160333
	Slange PE/C Ø 51 L=10 m	51	10	40160334
	Slange PE/C Ø 51 L=30 m	51	30	40160335
	Hose PE/C with couplers	38	5	40160390*
	Hose PE/C with couplers	50	5	40160400**
	Slange PE/C-38 L=5m m/koblinger	38	5	43811001***
	Slange PE/C-51 L=7,5m med koblinger	51	7,5	43812103**

## Sugeslange PE/C










Bilde	Navn på datablad	Diameter (mm)	Length (m)	Model
	Slange PE/C-51 L=10 m m/koblinger	51	10	43812200**
	Hose PE/C-63 L=10m			40375955

\*Couplings included (M40 & F40)

\*\*Couplings included Ø 51 mm

\*\*\*Couplings included

# Sugeslange PE/C

Tilbehør		Artikkelnummer
	Slangehylle 30 m 115x70	40195450
	Slangehylle 60 m 150x110	40195451
	Slangehylle 120 m 200x160	40195452
	Slange og ekst. hylle	40196370
	Slangeklemme 85	40903030
	Slangeklemme 56	40903170
	Slangeklemme 75	40903180
	Slangeklemme 112	40903210
	Slangeklemme 104-112 ABA Robust	40903270
	Endehylse PE d38 antistatisk m/hann	43819012
	Endehylse PE d38 antistatisk m/hunn	43819013