

PE 型抽排软管

应用领域：单一抽排软管，主要用于一般清洁。该软管不导电



温度范围: $-40^{\circ} \sim +60^{\circ} \text{ C.}$
最大真空度 50 kPa.

品名	PE 型抽排软管
Max vacuum (kPa)	50

PE 型抽排软管

[image]	产品名称	直径 (mm)	Length (m)	产品编号
	软管 PE 25, 长 10m	25	10	40160712
	软管 PE 32, 长 10m	32	10	40160722
	软管 PE 38, 长 5m	38	5	40160731
	软管 PE 38, 长 10m	38	10	40160733
	软管 PE 38, 长 20m	38	20	40160735
	软管 PE 51, 长 5m	51	5	40160741
	Hose PE 32, length 5m	32	5	40375953
	软管 PE 38, 长 5m, 带接头	38	5	40160370
	软管 PE 50, 长 5m, 带接头	50	5	40160380
	软管 PE 51, 长 20m	51	20	40160745
	PEFA hose d51 20m			43812300
	PE 防静电吸风管d51, 0.75m			43812400
	PE 防静电吸风管d51, 1.35m			43812500

PE 型抽排软管

附件		产品编号
	软管架, 30M 115x70	40195450
	软管架, 60M 150x110	40195451
	软管架, 120M, 200x160	40195452
	软管& 清灰套件支架	40196370
	软管夹, 85	40903030
	软管夹, 56	40903170
	软管管箍 $\Phi 75\text{mm}$	40903180
	软管管箍 112	40903210
	坚固型软管夹, 104-112 ABA	40903270
	End sleeve PE d32, antistatic	43819001
	End sleeve d38, pe, antistatic	43819011