

## FS 型抽排软管

---

应用领域：柔性软管，预埋钢筋螺旋用于释放静电。主要用于手持工具和平衡臂的抽排。











温度范围: 0 ~ +80 ° C.  
最大真空度60 kPa.

|                  |          |
|------------------|----------|
| 品名               | FS 型抽排软管 |
| Max vaccum (kPa) | 60       |
| Length (m)       | 15       |



## FS 型抽排软管

| [image]   | 产品名称               | 直径 (mm) | 产品编号     |
|---|--------------------|---------|----------|
|    | 软管 FS-25 L=15m 带螺纹 | 25      | 40160102 |
|    | 软管 FS-32 L=15m 带螺纹 | 32      | 40160152 |
|    | 软管 FS-38 L=15m 带螺纹 | 38      | 40160202 |
|    | 软管 FS-44 L=15m 带螺纹 | 44      | 40160223 |
|    | 软管 FS-51 L=15m 带螺纹 | 51      | 40160252 |
|   | 软管 FS-63 L=15m 带螺纹 | 63      | 40160263 |
|  | 软管 FS-38 L=5m 带接头  |         | 40160350 |
|  | 软管 FS-50 L=5m 带接头  |         | 40160360 |

## FS 型抽排软管

| 附件  |                           | 产品编号     |
|---|---------------------------|----------|
|    | 软管架, 30M 115x70           | 40195450 |
|    | 软管架, 60M 150x110          | 40195451 |
|    | 软管架, 120M, 200x160        | 40195452 |
|    | 软管& 清灰套件支架                | 40196370 |
|    | 软管夹, 85                   | 40903030 |
|    | 软管夹, 56                   | 40903170 |
|    | 软管管箍 $\Phi$ 75mm          | 40903180 |
|   | 软管管箍 112                  | 40903210 |
|  | 坚固型软管夹, 104-112 ABA       | 40903270 |
|  | 球阀, 38型, 353, PVC         | 40615210 |
|  | Ballvalve for 44 mm hoses | 40376978 |