

## Suction hose PVC

---






Application areas: Robust oil-resistant hose, smooth inside. Very good resistance to wear and ageing. Good resistance to fuels, oils, solvents, chemicals and grease.

- Temp. range: -20° to +70 °C.

Product name	Suction hose PVC
Max vacuum (kPa)	84
Diameter (mm)	51










## Suction hose PVC

Image	Description	Length (m)	Model
	PVC Hose, Ø 51 mm. length 10 m with conductive couplers	10	43822200*
	PVC Hose, Ø 51 mm. length 25 m	25	43822300**
	PVC Hose, Ø 51 mm. length 25 m with conductive couplers	25	43822301*
	PVC Hose, Ø 51 mm. length 7,5 m with conductive couplers	7,5	43822600*

\*Couplings included, Ø 51 mm

\*\*Without couplers

## Suction hose PVC

Accessory		Part No
	Hose Shelf 30M 115x70	40195450
	Hose Shelf 60M 150x110	40195451
	Hose Shelf 120M 200x160	40195452
	Hose & Add.shelf	40196370
	Hose clamp 56	40903170
	Hose clamp 75	40903180
	Hose clamp 85	40903030
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270