

与SF51型接头连接



51mm清洁设备用于重负荷应用环境的清洁,例如切屑和重型工业材料。几乎所有产品都是导电的,可以用在ATEX分类区域,请查阅资料手册获取更多信息。

铝制的落地式吸嘴附带滚轮和可替换的橡胶边/毛刷湿吸尘 抗静电

品名 地面清洁系统: 51 mm



[image]	产品名称	产品编号
	Floor cleaning equipment width 400 mm with small nylon wheels and rubber lips, d51 mm	42932000*
-5	Floor cleaning equipment width 500 mm with small nylon wheels 51 and rubber lips	42932100*
15	Floor cleaning equipment width 600 mm with small nylon wheels and rubber lips, d51 mm	42932200*
4	Floor cleaning equipment width 400 mm with large rubber wheels 51 and rubber lips	42932300*
1-	Floor cleaning equipment width 400 mm without wheels for wet suction, with rubber lips, d 51 mm	42932500**
1-	Floor cleaning equipment width 400 mm without wheels for dry suction 51, with brushes	42932800*
	Floor cleaning equipment width 450 mm with wheels for wet and dry suction and with brushes, d51 mm	42934200
	清洁设备,CE 500 W=500 D=50 (2x5m PE)	40191120
	清洁设备,CE 500 W=500 D=50 (2x5m PE/C)	40191190*

^{*}ATEX:适用于可燃粉尘(20区,21区,22区)。确保抽排设备接地。不能用于可燃气体环境和易爆物质的抽排。 **ATEX – Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA,IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials



	附件	产品编号
4	地面吸嘴,宽400 mm 带尼龙小轮	43840100*
	地板吸头 d51/450	43840001
4	地面吸嘴,宽500 mm 带尼龙小轮, 51	43840150*
	地面清洁设备,宽600 mm 带尼龙小轮	43840200*
⋖.	地面吸嘴,宽400 mm 带橡胶大轮,51	43840250*
⋖.	地面吸嘴,宽500 mm 带橡胶大轮	43840300*
⋖.	地面吸嘴,宽600 mm 带橡胶大轮	43840350*
	清洁管道,长1100 mm, 51 mm	43842001**
	弯头, 51 mm	43842150**
	地面吸嘴,宽400 mm 不带轮,湿式抽吸	43840500**
>	地面吸嘴,宽400 mm 不带轮,干式抽吸,51	43840550***
1	直管,D=50 L=500	40195940
	弯管,D=50 GMW	40195950
4	Floor suct head d51/300	43840103
⋖.	Floor suct head d51/300/65	43840251
	Nozzle floor brush L=500 GMW	40193500***
	Nozzle floor L=500 rubber GMW	40193650
	软管&清灰套件支架	40196370
	软管架,60M 150x110	40195451
	Pipe bend d51 ss	43999663
	SF51, 母旋转接头 dia 51	43930101
	SM 51, 公旋转接头 dia 51	43930102



附件		产品编号
	SV51, Flap valve swivelling 51	43885001

^{*}ATEX – This product is suitable to be used as cleaning equipment for combustible dusts with MIE (minimum ignition energy) >1 mJ. Product is to be properly earthed to the extraction unit. Not for usage in combustible gas atmospheres or extraction of xplosive materials.

^{**}ATEX – Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA, IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials

^{***}ATEX – This product is suitable to be used as cleaning equipment for combustible dusts with MIE (minimum ignition energy) >1 mJ. Product is to be properly earthed to the extraction unit. Not for usage in combustible gas atmospheres or extraction of explosive materials.