

# FilterBox 10A NANO

Automatically cleaned for light to medium dust & fume applications.

---

## FilterBox 10A NANO



When mobility, flexibility and a compact footprint is key, a mobile solution is often the best way to avoid contaminant exposure. Nederman FilterBox range of mobile dust and fume extraction units are easy to move around your factory to wherever the extraction is needed. The wide product range makes it easy to find a model with the capacity, features and filter type needed.

The FilterBox 10A+ is equipped with a N24 fan for a maximum air flow capacity of 1 000 m<sup>3</sup>/h (600 CFM). The nanofiber media technology utilized in the extra large 17m<sup>2</sup> (183 ft<sup>2</sup>) cartridge is ideal for frequent welding. It offers significant performance advantages like higher efficiency and surface loading properties which results in more effective filter cleaning and longer cleaning intervals. Advantages that will impose benefits in terms of filter life, productivity and lower cost of ownership.

The unit has an advanced filter control system indicating the pressure drop with a series of LED's as well as on the LCD display. When the air flow is too low an aural alarm precedes the automatic, motorized compressed air cleaning sequence. An integrated silencer reduces noise from the fan and outlet air. Additional protection from harmful particles is provided if a HEPA filter is installed (optional). FilterBox 10A+ is available as a mobile unit on wheels but can be fixed mounted with an accessory kit.

Note! FilterBox is not for use in environments where combustible dust or gases are present, and it is not for use in filtering combustible dust or gases.

- Automatically operated filter cleaning with compressed air for long filter life.
- LCD panel with operating status and menu system for parameter setup and settings.

Possibility to connect a welding sensor clamp to automatically start the fan.

- Automatic damper preventing dust from leaking out while cleaning.
- Dust free filter replacement and emptying of dust bin.
- MERV 15 rated filter \*ASHRAE Standard 52.2, 2017, third party tested.

Approved for welding fumes category W3 according to ISO 21904-1, third party certified


Nom du produit	FilterBox 10A NANO
Niveau sonore (dB(A))	66
Classe de protection	IP 54
Efficacité de filtration (%)	99,9
Installation	Intérieur

# FilterBox 10A NANO

Matériel	Casing in rotomoulded plastic
Volume du seau (l)	15
Diamètre du bras d'extraction (mm)	160
Débit (m <sup>3</sup> /h)	1000
Surface filtrante (m <sup>2</sup> )	17
Fréquence (Hz)	50
Type de filtre	Filtre à cartouche
Nombre d'éléments filtrants	1
Média filtrant	Nanofiber
Prise électrique	Sans
Mounting	Mobile
Max airflow (m <sup>3</sup> /h)	1000
Poids (kg)	102
Filter cleaning method	[CompressedAir]
Note	Filter class F9 (EN779), MERV 15 (ASHRAE 52.2)
Filter Area (m <sup>2</sup> )	











## FilterBox 10A NANO

[image]	Longueur du bras (m)	Tension (V)	Nombre de phases	Puissance (kW)	[model]
	3 (Original)	230	3	0,9	12694663*
	Without	400	3	0,9	12695763*
	3 (Original)	230	1	0,75	12694863*
	3 (Original)	400	3	0,9	12694763*

\*Filter class F9 (EN779), MERV 15 (ASHRAE 52.2)

## FilterBox 10A NANO

	[accessory]	[partno]
	Filter NANO-FB-17	12377251
	Filter PTFE-FB-13	12377252
	Sensor Clamp	14372199
	HEPA filter H14 10m2 Filterbox	12376756
	Lampe LED / interrupteur de ventilateur d'origine	10376922
	Pare-étincelle pour hotte d'origine/NEX MD	10551335
	HEPA filter H13 10m2 Filterbox	12376615
	Spot d'origine, (LED) 24 V, 5 W	12376616*
	Bags for Filterbox dust bin, 10pcs	12376618
	Sortie avec raccord de conduite D=200 mm	12376749
	Twin Module blue	12376801

\*Interrupteur pour éclairage (pas de démarrage de ventilateur)