

FlexPAK

Frequency controlled compact high vacuum dust collector unit to be used for many different applications. Typically 2-10 users.



The FlexPAK is a frequency controlled high vacuum dust collector unit. The unit is designed for the extraction of welding fume, grinding dust, metal chips etc. FlexPAK is suitable for cleaning the workplace, the shop floor and machines. It is also very suitable for on-tool and on-torch applications. FlexPAK regulates the speed of the motor automatically depending on the vacuum demand. Compared to traditional controllers, FlexPAK provides an optimal, and well-balanced vacuum according to the need, ensuring energy-saving operation. The FlexPAK have different running modes to meet specific customer needs. The FlexPAK can easily switch between generating as much vacuum as possible, typically for applications with long piping or material transportation, or maintaining a constant vacuum level, typically useful for welding fume or grinding dust applications.

- Easy to install
- Built in PLC functions
- Low operating cost
- Reliable
- Suitable for a wide range of applications

Nome do Produto	FlexPAK
Nível de ruído (dB(A))	70
Classe de proteção	IP 42
Instalação	Interior, Exterior
Material	C2 according to ISO 12944-2
Adequado para poeiras combustíveis	False
Método de limpeza do filtro	Pulso de ar em contra fluxo
Material reciclável (%)	93,6
Application	Granulado, Areia, Fumos, Granalha, Poeira
Pressão de serviço (kPa)	20-35
Volume do balde (l)	70
Máx. caudal (m ³ /h)	1300
Área Filtrante (m ²)	6
Frequência (Hz)	50/60
Nº de fases	3
Tipo de filtro	Filtro de velas
Número de elementos filtrantes	1
Material Filtrante	Polypropylene
Compressed air requirement	6-7 bar
Max vacuum (kPa)	35
Inlet	150 mm
Peso (kg)	439





Areia Poeira Fumos Granalha Granulado



FlexPAK

Descrição	Voltagem (V)	Noise level (dB(A))	Potência /kW)	[model]
FlexPAK 400V 50/60Hz	400		18,5	40050361
FlexPAK 460V 50/60Hz	460		21,5	40050360
FlexPAK 380V 50/60Hz	380	70	18,5	40050363
FlexPAK 400V 50/60Hz IOT EU	400	70	18,5	40050366
FlexPAK 400V 50/60Hz IOT Adv EU	400	70	18,5	40050367

FlexPAK

[accessory]		[partno]
	Fire alarm complete.	40116540
	Replacement plastic Bag 730x900, 20pcs, in dissipative material for EX applications	40118800
	Level Indic. BLI 10-40VDC Compl.	40780710

FlexPAK

