

Welding curtains



Standard sized curtains (see below) provided with 50 mm welded seam all around and with snap-fasteners on both sides for joining to obtain total desired width. Supplied with reinforced holes in the upper edge and steel suspension rings. All standard curtains are made of pliable self extinguishing PVC material with flash point 320-390°C. Width: 1400 mm, Thickness: 0.40-0.50 mm. The Nederman yellow and clear transparent curtains are used for glare, splatter, grinding, dust etc. but are not aimed for welding, unlike our EN1598 compliant curtains that are ideal for welding applications.

| | |
|--------------|------------------|
| Product name | Welding curtains |
|--------------|------------------|



Welding curtains

| Description | Model |
|---|-------------|
| Protection curtain transparent clear 1,4 x 1,8 m, h= 1800 mm | 60313624 |
| Protection curtain transparent clear 1,4 x 2,4 m, h= 2400 mm | 60313625* |
| Protection curtain transparent clear 1,4 x 2,8 m, h= 2800 mm | 60313626* |
| Protection curtain transparent yellow 1,4 x 1,8 m, h= 1800 mm | 60313524* |
| Protection curtain transparent yellow 1,4 x 2,4 m, h= 2400 mm | 60313525* |
| Protection curtain transparent yellow 1,4 x 2,8 m, h= 2800 mm | 60313526* |
| Welding curtain dark green 1,4 x 2,4 m, h= 2400 mm | 60313125** |
| Welding curtain dark green 1,4 x 2,8 m, h= 2800 mm | 60313126*** |
| Welding curtain transparent bronze 1,4 x 1,8 m, h= 1800 mm | 60313224** |
| Welding curtain transparent bronze 1,4 x 2,4 m, h= 2400 mm | 60313225*** |
| Welding curtain transparent bronze 1,4 x 2,8 m, h= 2800 mm | 60313226** |
| Welding curtain transparent green 1,4 x 1,8 m, h= 1800 mm | 60313424** |
| Welding curtain transparent green 1,4 x 2,4 m, h= 2400 mm | 60313425*** |
| Welding curtain transparent green 1,4 x 2,8 m, h= 2800 mm | 60313426** |
| Welding curtain transparent orange 1,4 x 1,8 m, h= 1800 mm | 60313324*** |
| Welding curtain transparent orange 1,4 x 2,4 m, h= 2400 mm | 60313325** |
| Welding curtain transparent orange 1,4 x 2,8 m, h= 2800 mm | 60313326*** |

*Total width of curtains shall be 10% longer than total required screening length.

**Cert. EN 1598

Total width of curtains shall be 10% longer than total required screening length.

***Cert. EN 1598.

Total width of curtains shall be 10% longer than total required screening length.