

The hose is constructed of a medium weight clear static dissipative polyurethane reinforced with a bronze coated spring steel wire helix



The static dissipative hose provides great abrasion resistance and high tear strength as well as superior chemical resistance, excellent flexibility, and tolerance for applications with wide temperature ranges (-65° F to 225° F).

• Sold in 5 lengths, examples 5', 10', 15'.

Suitable markets (Nordfab)	Americas, South America
Material	Polyurethane
Length (unit)	in



Image	Short description	Legacy Item No.	Diameter A	Weight	Model
	Hose Static Dissipative Polyurethane 4in	3279-0400-000000	4	0.7 lbs/ft	8010004040
	Hose Static Dissipative Polyurethane 5in	3279-0500-000000	5	0.9 lbs/ft	8010004041
	Hose Static Dissipative Polyurethane 6in	3279-0600-000000	6	1 lbs/ft	8010004042
	Hose Static Dissipative Polyurethane 8in	3279-0800-000000	8	1.5 lbs/ft	8010004043
	Hose Polyurethane 10in	3279-1000-000000	10	1.6 lbs/ft	8010004037
	Hose Static Dissipative Polyurethane 12in	3279-1200-000000	12	2 lbs/ft	8010004038



Accessory	Part No
Bridge Hose Clamp 304SS 3in	8010002517
Bridge Hose Clamp 304SS 4in	8010002518
Bridge Hose Clamp 304SS 5in	8010002519
Bridge Hose Clamp 304SS 6in	8010002520
Bridge Hose Clamp 304SS 7in	8010002521
Bridge Hose Clamp 304SS 8in	8010002522
Adapter Hose	8040401963
Adapter Hose	8040401965
Adapter Hose	8040401966
Adapter Hose	8040401967
Adapter Hose	8040401968
Adapter Hose	8040401969
Adapter Hose	8040401970
Adapter Hose	8040401971
Adapter Hose	8040401972
Adapter Hose	8040401973
Adapter Hose	8040401974
Adapter Hose	8040401975
Adapter Hose	8040401976
Adapter Hose	8040401977
Adapter Hose	8040401978
Adapter Hose	8040401979



Accessory	Part No
Adapter Hose	8040401980
Adapter Hose	8040401981
Adapter Hose	8040401982
Adapter Hose	8040401983
Adapter Hose	8040401984