

Self-contained, cartridge dust collectors for ambient air cleaning





MCP-12S-APT, High version

The MCP-12S-APT Air Purification Tower (APT) is an innovative solution for ambient clean air in factories with welding fumes or suspended dust. It can be used as a standalone unit or in a network of units, depending on the workshop's size and layout. It is ideal for situations where source capture is impractical or insufficient for comprehensive air cleaning.

The Air Purification Tower has various applications, such as large part welding, areas with cranes or obstructions that prevent overhead ducts, areas that need a lot of movement or general ventilation for nuisance dusts.

- · Compact and efficient design.
- Twelve high-capacity, patented cartridge filters with fireretardant, Nanofiber media increase efficiency, reduce energy consumption, extend filter life, and shrink footprint by 20% compared to previous generations.
- Flexible and adaptable configuration.
 Low and High models with 60 individually adjustable nozzles can cover simple and complex arrangements. The High model has a clean air return header that can rotate 360° and extend in height, allowing the unit to deliver air in optimal airflow patterns in complex environments.
- Powerful and quiet fan.
 A robust and reliable Combifab-F series fan, enclosed in a sound attenuation chamber, keeps sound levels below 72 dB(A).
- Integrated, user-friendly controller.
 Operates fan and filter cleaning, with clear visualization of device status. It also has remote/start-stop signals and timers to automate operation. Each model can have a Variable Frequency Drive (VFD) for enhanced airflow control and energy efficiency.
- Simple and convenient installation and maintenance.
 Delivered as three pre-mounted and pre-wired components, and once installed, has single-side access to all vital unit components. A large dust bin ensures extended maintenance intervals.

Наименование товара	MCP-12S-APT Air Purification Tower
Уровень шума (дБ(А))	72 (at 1m (3.28 ft.) from unit at 1,6 m (5.25 ft.) height
Потребление сжатого воздуха	16,5 NI/cleaning puls (0.6 cfm)
	50 NI/min at 20 s interval (1.6 cfm/min)
	165 NI/min after cleaning (5.9 cfm/min)
Установка	Снаружи помещения
Материал	Galvanised sheet metal
Метод очистки фильтра	Импульсная продувка
Применение	дым
Рабочее давление (кПа)	Negtive pressure max 6 kPa (24 inch / 6000 Pa)



Объем пылевого контейнера (л)	50 I with wheels (13 gal.)
Площадь фильтра (м²)	158 (1700 ft²)
Производительность (макс. воздушный поток м3/час)	10000 (5900 cfm)
Рабочая температура	-20°C to 70 °C (-4°F to 158°F)
Напряжение (В)	400
Частота (Гц)	50
Тип фильтра	Картриджный фильтр
Количество фильтроэлементов	12
Фильтрующий материал	SC178 polyester material with nanofiber (80% cellulose, 20% polyester), suitable for fine dust and welding fumes
Мощность (кВт)	10.0





лым



[image]	Вес (кг)	[model]
	900	73001823
	950	73001824
	900	73002325
	950	73002326




[accessory]		[partno]
	Filter regulator	55999315
The state of the s	Level indicator for dust bin	55999316
	Lifiting device for fork lift	55999319
	4 m connection cable set with CEE plug (pre-mounted)	55999328
	Duct piece for room cleaning Ø710 (28 inch)	7945520




10-04-2024

MCP-12S-APT Air Purification Tower



Dimensions MCP-12S-APT LOW version





Dimensions MCP-12S-APT HIGH version