

## FilterBox 10M

Manually cleaned for light to medium dust  
& fume applications.

---

## FilterBox 10M



The FilterBox 10M is equipped with a N24 fan for a maximum air flow capacity of 1 000 m<sup>3</sup>/h (600 CFM). An integrated silencer reduces noise from the fan and outlet air.

The unit has a filter supervision system which indicates when the air flow is too low. Depending on the model, it is equipped with mechanical cleaning for dust applications or a combination of mechanical and compressed air cleaning for fumes and dust. FilterBox 10M is available either as a mobile unit on wheels or attached to a floor stand. Additional protection from harmful particles is provided if a HEPA filter is installed.

For dust applications, the unit is cleaned mechanically. For welding fumes it uses a combination of mechanical and compressed air cleaning.

For welding applications, compressed air cleaning is required.

Note! FilterBox is not for use in environments where combustible dust or gases are present, and it is not for use in filtering combustible dust or gases.

- User friendly and superior filter cleaning, mechanical and/or with compressed air for long filter life
- Automatic damper preventing dust from leaking out while cleaning
- Dust free filter replacement and emptying of dust bin
- Third party approval for welding fumes category W3 according to EN 15012-1
- Approved for welding fumes category W3 according to EN 15012-1, third party tested.






Product name	FilterBox 10M
Noise level (dB(A))	66
Protection class	IP 54
Filter efficiency (%)	99
Compressed air requirement	DIN ISO 8573-1, class 5/5/4 (7 bar)
Installation	[Indoor]
Material	Casing in rotomoulded plastic
Dustbin volume (l)	15
Extraction arm diameter (mm)	160
Filter Area (m <sup>2</sup> )	13
Frequency (Hz)	50
Filter type	[cartridge]
Number of filter elements	1
Filter material	Polyester PW13
Electric plug	without
Max airflow (m <sup>3</sup> /h)	1000
Weight (kg)	102
Filter cleaning method	Mechanical, Compressed air

# FilterBox 10M










Note	
Filter Area (m <sup>2</sup> )	



## FilterBox 10M

Image	Description	Arm length (m)	Power Voltage (V)	No of phases	Mounting	Power (kW)	Model
	FilterBox 10 M	3	400	3		0,9	12652363
	FilterBox 10 M	3	230	1		0,75	12652463
	FilterBox 10 M	3	110	1		0,75	12652563
	FilterBox 10 M	Without	400	3		0,9	12684963
	FilterBox 10 M	Without	400	3		0,9	12686563

## FilterBox 10M

	Accessory	Part No
	Spotlight original, (LED) 24V, 5W	12376616*
	Handle eQ Filterbox	12376617
	Outlet with duct connection D=200mm	12376749
	Spark protection for Original/NEX MD-hood	10551335
	Filter-PW-FB-13	12332672
	Filter PWA-FB-15	12371412
	HEPA filter H13 10m2 Filterbox	12376615
	HEPA filter H14 10m2 Filterbox	12376756
	Bags for Filterbox dust bin, 10pcs	12376618
	Twin Module blue	12376801
	Filter PTFE-FB-13	12377252

\*Switch for light (no fan start)

# FilterBox 10M

