

## Industrial vacuum cleaner 30 S

Economical and easy to handle three phase compact portable dust collectors



These three phase compact portable dust collectors are efficient, economical and easy to handle. The dry vacuums are very easy to dismantle and clean. The location of the (optional) micro filter prevents contamination of the pump. The forward/reverse switch saves time when moving between work sites with different phase sequence.







- Easy to handle
- High filtration efficiency
- Economical
- Micro filter as option

Product name	Industrial vacuum cleaner 30 S
Noise level (dB(A))	71
Protection class	IP55
Filter efficiency (%)	99
Installation	Indoor
Material	Housing in sheet metal.
Filter cleaning method	Reverse air pulse
Application	Dust, Granulate, Fumes
Dustbin volume (l)	25
Max Airflow (m3/h)	240
Hose Diameter (mm)	38
Hose length (m)	5
No of phases	3
Filter type	Bag
Filter material	
Noise level (dB(A))	
Weight (kg)	74
Hose length (m)	
Hose diameter (mm)	



Granulate Fumes Dust










## Industrial vacuum cleaner 30 S

Image	Description	Power Voltage (V)	Frequency (Hz)	Max vacuum (kPa)	Power (kW)	Model
	30 S 400V 50Hz	400	50	30	3	40055800*
	30 S 230V 50Hz	230	50	30	3	40055810*
	30 S 230V 60Hz	230	60	30	3,5	40055830*
	30 S 460V 60Hz	460	60		3,5	40055840*
	30 S 380V 60Hz	380	60		3,5	40055860*
	30 S 400V,50Hz,antistat+mi cro filter	400	50		3	40055870**

\*Includes cleaning equipment.

\*\*Includes cleaning equipment. Antistatic filter class M and microfilter included

## Industrial vacuum cleaner 30 S

	Accessory	Part No
	Filter package 1,1m2 PP	40114160
	Replacement Microfilter (D=140 x 350)	40114110
	Extended brush, 169 x 54 mm.	40190020*
	Brush hygiene, food industry	40190030*
	Round rubber brush with swivel top	40193080*
	Circular crevice nozzle in plastic. Length: 360 mm. Width: 45 x 10 mm.	40193090*
	Circular crevice nozzle in steel Length: 310 mm. Width: 55 x 15 mm	40193620**
	Rubber nozzle for confined spaces. Length: 230 mm. Width: Ø 32-38 mm.	40193130*
	Rubber nozzle for confined spaces. Length: 230 mm. Width: Ø 25-32 mm.	40193110*
	Nozzle crevice plastic 60x15 D=40	40377194
	Replacement bagfilter (PTFE)	40119422

\*ATEX - Suitable for combustible dust (zone 20,21,22). Ensure earthing to extraction unit. Not to be used in combustible gas atmospheres or extraction of explosive materials.

\*\*ATEX - Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA , IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials