

Physical-Technical Testing Institute Ostrava - Radvanice



(1) Supplementary EU - Type Examination Certificate No.2

Equipment or Protective Systems Intended for Use in Potentially Explosive Atmospheres (Directive 2014/34/EU)

(3) EU - Type Examination Certificate number:

FTZÚ 18 ATEX 0147X

(4) Product: Explosion isolation flap valve, type CARZ-NS DN160 - DN 250

(5) Manufacturer: Nederman Manufacturing Poland Sp. z o.o.

(6) Address: Okólna 45A, 05-270 Marki, Poland

- (7) This supplementary certificate extends EU Type Examination Certificate No. FTZÚ 18 ATEX 0147X to apply to products designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.
- (8) The Physical-Technical Testing Institute, Notified Body number 1026, in accordance with Articles 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26.02.2014, certifies that this product, as modified by this supplementary certificate, has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.
- (9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 16447:2014; EN ISO 80079-36:2016

- (10) If the sign "X" is placed after the certificate number, it indicates that the product is subject to Specific Conditions of Use specified in the schedule to this certificate.
- (11) The marking of the product shall include the following:

⟨έχ⟩ D St2

ᢄx II 1/2 D Ex h IIIC T75°C Da/Db

(12) This certificate is valid till: 31.12.2029

Responsible person:

V 2. 9907

Dipl. Ing. Lukáš Martinák Head of Certification Body



Date of issue: 12.12.2024

Page: 1/3

This certificate is granted subject to the general conditions of the FTZÚ, s.p. This certificate may only be reproduced in its entirety and without any change, schedule included.



Physical-Technical Testing Institute Ostrava - Radvanice

(13)

Schedule

Supplementary EU - Type Examination Certificate No. 2 (14)to FTZÚ 18 ATEX 0147X

(15) Description of the variation to the Product:

The subject of this supplementary certificate is:

- Extension of certificate validity.

The construction, materials and technical parameters of certified product remain unchanged.

The explosion isolation flap valve type CARZ-NS are designed as explosion pressure resistant equipment, which is able to prevent a transmission of dangerous effects of explosion, pressure wave, and flames in one direction and separates volumes with potentially explosive atmosphere of industrial dusts. In opposite direction back pressure flaps enable transfer of powdery flammable material. Type series of explosion isolation flap valves CARZ-NS works as protective system if requirements in article (17) are fulfilled.

(16) Report Number:

18/0147/2

- (17) Specific Conditions of Use:
 - Ambient temperature range: -from -20°C to 60°C.
 - a) Organic dust: K_{st,max} = 300 bar.m.s⁻¹, MESG ≥1,3 mm

The maximum dust concentration in the ducting is without the limit.

Push and pull situation allowed, vessel is protected with non-reclosing vent

devices, with reclosing vent devices or suppression.

b) Metal dust:

 $K_{\text{st,max}}$ = 260 bar.m.s⁻¹, MESG \geq 1,3 mm, MIT = 710°C

The maximum dust concentration in the ducting has to be under the LEL (Lower

Explosive Limit) value of the dust.

Pull situation allowed, vessel is protected with non-reclosing vent devices (this

excludes e.g. suppression and venting with reclosing vent devices).

- Straight ducting with up to maximum of 2 bends 90° between the protected vessel and the flap. 3.
- Minimal installation distance is 5 m, maximal installation distance is 10 m. 4.
- 5. Minimal vessel volume is 0,46 m³.
- Maximum reduced pressure in the vessel $p_{red,max} = 0.5$ bar. 6.

Responsible person:

Dipl. Ing. Lukáš Martinák Head of Certification Body



Date of issue: 12.12.2024

Page: 2/3

This certificate is granted subject to the general conditions of the FTZÚ, s.p. This certificate may only be reproduced in its entirety and without any change, schedule included.



Physical-Technical Testing Institute Ostrava - Radvanice

(13)

Schedule

(14) Supplementary EU - Type Examination Certificate No. 2 to FTZÚ 18 ATEX 0147X

- (17) Specific Conditions of Use: continuation
 - 7. Explosion resistance of the flap $p_{max} = 1$ bar.
 - 8. The maximal speed flow is 35 m.s⁻¹.
 - Maximum allowable opening angle of the blade to the vertical is 45°.
 - The product has to be installed so that the propagating brush discharges on the external surface of the device are avoided.
 - 11. The electrical devices installed together with the back pressure flap must have the type of protection corresponding with the defined explosive zone.
- (18) Essential Health and Safety Requirements:

Compliance with the Essential Health and Safety Requirements is covered by standards mentioned in clause (9) of this supplementary certificate.

(19) Drawings and Documents:

Number	Sheets	Issue	Date	Description
CARZ_NS_G	2	D	11.12.2024	Drawing
CARZ_NS_WD	2	D	11.12.2024	Drawing
LABEL_CARZ_NS	1	С	11.12.2024	Drawing
IHA_CARZ-NS	2	3	11.12.2024	Risk analysis

Rest of technical documentation remain unchanged and is listed in the original certificate and its supplementary certificate no. 1.

Responsible person:

V 2. 990

Dipl. Ing. Lukáš Martinák Head of Certification Body



Date of issue: 12.12.2024

Page: 3/3