

PRODUCT LEAFLET

NOM 11

Oil mist filter



NOM 11

- Low maintenance cost
- Self draining mist filter
- Easy to install
- High filtration efficiency
- Made to take up very little space with integrated fan for most models

Designed for lathing and milling applications, for machines stamping and pressing steel plates, industrial washing machines, abrasive water jets etc. In all metal fabrication with oil mist troubles, these filters will fit into a ducting system, connected to each machine. All units are equipped with pressure gauge for control of filters as well as a indication for need of cleaning (self draining). Suitable for emulsion mist.

NOM 11

[ProductCertifications]	[ce]
[ProductNoiselevel]	66,4
[ProductProtectionclass]	IP55
[ProductFilterefficiency]	97.5
[ProductCompressedairconsumption]	No
[ProductInstallation]	[Indoor]
[ProductMaterial]	Housing made in oil resistant wet painted sheet metal.
[ProductSuitableForCombustableDust]	False
[ProductMaterialrecycling]	86
[ProductFilterArea]	8.5
[ProductCapacityMax]	1100
[ProductOperatingTemperature]	5 - 60 C
[ItemFilterType]	[cartridge]
[ItemNbrofFilterElements]	1

Nederman NOM 11

Models

Item number	[ItemPowerVoltage]	[ItemFrequency]	[ItemNoofphases]	[ItemAmperage]
12621768	230	50	1	5,7
12622268 ^[1]	400/230	50	3	1,7/2,9
12622668 ^[2]				
12622568 ^[3]				
12621868 ^[1]	230	50	1	5,7
12622168	400/230	50	3	1,7/2,9

 $^{^{[1]}}$ Includes HEPA filter with 16 sqm filterarea and with 99,97 % efficiency. $^{[2]}$ Delivered without fan. Includes HEPA filter with 16 sqm filterarea and with 99,97 % efficiency. $^{[3]}$ Delivered without Fan.

Accessories

	Accessory	Item number
Machine	FMS 1.6 -2.5 Fan Manual Starter	14502237
	Silencer NOM 11	12373649
. 4	Container NOM 11, 18, 28	12373651
2	Hose with oil trap NOM	12373652
	Main filter 8,5m2 NOM 11	12373654
Î	HEPA 16m2 NOM 11	12373646
	Coarse pre-filter	12376294

Y = Efficiency (%), X = Particle size (μm) A = NOM filter, B = Centrifugal filter A, C = Centrifugal filter B Efficiency of NOM main filter compared to typical centrifugal filters, tested with DOP.

