

PRODUCT LEAFLET

# Hose Reel 893

Versatile hose reel that can be mounted on wall or ceiling.



2025-05-20

#### Nederman

Hose Reel 893

#### Hose Reel 893

- Open design for easy cleaning and servicing
- Unique stand design offers mounting flexibility

Medium-sized reel in robust open design. Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling. Versatile and easily installed in industrial and workshop environments.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB 2025-05-20

#### Nederman

Hose Reel 893

### Hose Reel 893

[ce]
100
Compressed air, Water, Water high pressure, Oil, Food, [grease]
1
Black drum / Blue cover
14,5
Standard
Spring

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB 2025-05-20

3/6

2/6

### Nederman

Hose Reel 893

## Models

	ltem number	[ItemHoseMedia]	[ItemDeliveredWithHose]	[itemDistributionHoseLength]	[ItemDistributionHoseDlameter]	[ItemMaxworkingpressureHCR]	[ItemMaximumPossibleHoseLength]	[ItemTypeofhose]
Í	30800793	Compressed air, Water	[Without]	10	125	15	10	
<b>I</b>	30800393	Compressed air, Water	[Without]	15	10	15	15	
Ø	30800693	Compressed air, Water	[With]	15	10	15		[B]

	ltem number	[ItemHoseMedia]	[ItemDeliveredWithHose]	[ItemDistributionHoseLength]	[ItemDistributionHoseDiameter]	[ItemMaxworkingpressureHCR]	[ItemMaximumPossibleHoseLength]	[ItemTypeofhose]
1=Q.0-	30801793	Water high pressure	[Without]	15	10	25	15	
Ø	30801893	Water high pressure	[With]	15	10	25		[G]
Ő	30802693	[grease]	[With]	15	6	35		01
Ő	30801693	Oil	[With]	10	125	7,5		[0]
Í	30800893	Compressed air, Water	[With]	10	125	15		[8]
1-Q2-	30801593	Oil	[Without]	10	125	7,5	10	
Ø	30802593	[grease]	[Without]	15	6	35	15	
1-Q2.	30804993 <sup>[1]</sup>		[Without]	10	125		10	
()	30801093	Compressed air, Water	[With]	10	125	2		(E)
(1)								

4/6

<sup>[1]</sup> For suction hose

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

2025-05-20

### Nederman


# Hose types

[HoseType]	[HoseSpecification]	[HoseTemperatureRange]	[HoseFittingDistribution]	[HoseFittingInlet]	[HoseConnectionDistribution]	[HoseConnectionInlet]
В	Cover in NBR/PVC and inner tube in NBR. Syntethic textile braid	-30 - 100	Male, chrome plated		Hose nipple + clip	Hose nipple 1/2" + clip
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Syntethic textile braid	-30 - 100	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, chrome plated. With rubber hose grip	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
1	Cover and inner tube in syntetic, oil resistant rubber. Double steel braid	-40 - 100	Female 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone

#### Accessories

	Accessory	Item number
D	Roller guide.	30341550
	Pivoting bracket.	30372407
1	Water gun in chromium plated brass. Max. temperature 95°C	30400110
	Water gun in stainless steel 316. Max. temperature 95°C	30400210
<b>A</b>	Watergun EX	30400211
	Water gun in stainless steel 316. Max. temperature 95°C	30400310
~	Air gun, standard.	30410110
	Swivelling coupling 3/B(m)-3/B(m)HP	30431310

Hose Reel 893



6/6

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB 2025-05-20