

PRODUCT LEAFLET

# Suction hose PE/C



## Suction hose PE/C















- ✓ Smooth bore conductive hose.
- ✓ Max. vacuum 50 kPa.
- ✓ Temp. range: -40 °C to +60 °C.
- ✓ Conductivity <  $10^6 \Omega/m$

Application areas: Light and flexible extraction hose. Mainly suited for cleaning and where exceptional conductivity for static electricity is required.




# Suction hose PE/C

[ProductStandards]	Designed for ISO 21904 compliance
--------------------	-----------------------------------

## Models

	Item number	[ItemDiameter]
	40160305	25
	40160311	32
	40160313	32
	40160315	32
	40160321	38
	40160322	38
	40160323	38
	40160331	51
	40160333	51
	40160334	51
	40160335	51
	40160390 <sup>[1]</sup>	38
	40160400 <sup>[2]</sup>	50
	43811001 <sup>[3]</sup>	38

Models










	Item number	[ItemDiameter]
	43812103 <sup>[2]</sup>	51
	43812200 <sup>[2]</sup>	51
	40375955	

<sup>[1]</sup> Couplings included (M40 & F40)

<sup>[2]</sup> Couplings included Ø 51 mm

<sup>[3]</sup> Couplings included

## Accessories

	Accessory	Item number
	Hose Shelf 30M 115x70	40195450
	Hose Shelf 60M 150x110	40195451
	Hose Shelf 120M 200x160	40195452
	Hose & Add.shelf	40196370
	Hose clamp 85	40903030
	Hose clamp 56	40903170
	Hose clamp 75	40903180
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270
	End sleeve PE d38 antistatic w/male	43819012
	End sleeve PE d38 antistatic w/fema	43819013

