

PRODUCT LEAFLET

# Balance Arm

Ergonomic, space saving and full suction to hard-to-reach areas



**Nederman** Balance Arm

### Balance Arm



Well balanced and flexible

Easy to operate

Universal

In order to gain maximum accessability, the balance extraction arm is built up with two gas damper balanced sections. The extractor has three swivel points, one at the base, one at the middle and one at the point where the nozzle is attached. The nozzle can therefore be moved to any chosen position within the reach of the balance arm. The arms can be equipped with all suction nozzles within the Nederman High Vacuum programme. The friction for sideways movement is adjustable. The balance arm can be mounted in three different ways: to a wall, to a work bench or to an extension arm.

Mounting bracket, nozzle (CWN-S or FWN), handle and hose (FS or WH hose) must be ordered seperately. Mounting bracket, nozzle, handle and hose are ordered separatley.

**Nederman** Balance Arm

## Balance Arm

**Nederman** Balance Arm

## Models

	Item number
Salvaria de la constante de la	40180000
Section Sectio	40180010
Salvarations	40180020

4/5

**Nederman** 

## Accessories

	Accessory	Item number
	Bench bracket BA	40180040
	Wall bracket BA	40180030
	Wall bracket BA 500mm	40180070
	Hose WH-38 L=10m m.spiral	40160292
	Hose WH-51 L=10m m.spiral	40160272
	EA250 Extension arm (2,5 m)	40180050
	EA450 Extension arm (4,5 m)	40180060
1	Nozzle FWN 200/50	40290110
	Nozzle FWN 400/50	40290120
	CWN-S 105/50 nozzle silencer	40290230
	CWN-S 105/63 nozzle silencer	40290240
	Nozzle CWN-S 105/50L silencer	40290270
<b>*</b>	Nozzle CWN-S 105/40	40290330
	SOV 50 Shut off valve	40140030
	SOV 40 Shut off valve	40142510
	Nozzle extension	40290200

Balance Arm