

PRODUCT LEAFLET

# Magna Stack

用于带垂直叠加功能的应急车辆的尾气抽排系统

# Magna Stack

- ✓ Capacity: 1 vehicle per system
- ✓ Exhaust pipes: vertical stacks
- ✓ Normal exit speed: up to 15 km/h, 10 mph
- ✓ For reverse-in vehicles
- ✓ Optional automatic start/stop device that offers: -Practical control of fan start/stop -Safe control of air quality (source ventilation automatically starts when vehicle engine starts) - Simple programming - Approval for radio equipment acc. to EC directives, FCC (USA) and IC (Canada)

MagnaStack为全自动抽排系统。设计为罩盖形的抽排装置在车辆回到停车场时自动连接垂直排气管。导向臂将横向可调罩定位至排气管。排气管用电磁铁锁至引擎盖。车辆驶向出口时，水平软管和排气罩沿导轨平稳滑动。在门口，电力自动关闭，立即将电磁铁和排气管从排气罩松开。

作业能力:每个系统1个载具排气管:垂直排气管正常排出速度高达15 km/h - 10 mph用于反转式载具可选自动启动/停止装置提供:

-实际控制风机启动/停止-安全控制空气质量(载具引擎启动时源通风自动启动)-简单编程

# Magna Stack

|    |    |
|----|----|
| 证书 | CE |
|----|----|

Models

|                                                                                     | Item number             | 软管直径 (毫米) | 软管长度 (米) | 重量 (公斤)  |
|-------------------------------------------------------------------------------------|-------------------------|-----------|----------|----------|
|    | 20804263 <sup>[1]</sup> | 160       | 3        | 4,5 kg/m |
|    | 20804363 <sup>[1]</sup> | 160       | 6        | 4,5 kg/m |
|    | 20804463 <sup>[1]</sup> | 160       | 9        | 4,5 kg/m |
|    | 20812663 <sup>[1]</sup> | 160       | 9,8      | 4,5 kg/m |
|    | 20804563 <sup>[1]</sup> | 160       | 12       | 4,5 kg/m |
|    | 20804663 <sup>[1]</sup> | 160       | 15       | 4,5 kg/m |
|    | 20805163                |           |          | 12       |
|  | 20371306                |           |          |          |
|  | 20371307                |           |          |          |

<sup>[1]</sup> 导轨, 配软管  $\varnothing$  160 mm (6")

## Accessories

|                                                                                     | Accessory                                   | Item number |
|-------------------------------------------------------------------------------------|---------------------------------------------|-------------|
|                                                                                     | 无线电发射机 GHz                                  | 20376723    |
|                                                                                     | 无线电接收器 GHz                                  | 20376724    |
|    | 手持无线电发射机GHz                                 | 20376725    |
|    | 无线广播系统的成套节目                                 | 20376726    |
|                                                                                     | 3HP/3PH/208-230V Auto-Start Control Console | 89116051    |
|                                                                                     | Aut-StCtrPnl3Hp/1Ph/208-230Vw/ASlbd         | 89116050    |
|                                                                                     | Nozzle 160 Oval w hose/spring 600 C         | 86900103    |
|                                                                                     | 6" HB Nozzle for Dual Pipe, Lower H         | 86900377    |
|                                                                                     | Nozzle 160 mm Oval w HT hose/spring         | 86900440    |
|                                                                                     | 5 in. Hb Nozzle, Only for Dual Pipe         | 86900374    |
|  | Radio receiver US version                   | 20377356    |

A; Pressure drop (Pa) B; Airflow (m<sup>3</sup>/h) C; Airflow (cfm) D; Pressure drop (in w.g.)

