

OMF 2000

FibreDrain® 可持续运行的油雾收集设备



OMF 2000

- ✓ 三级滤芯单元, 可选预过滤
- ✓ 观测每层滤芯单元的压强下降
- ✓ 延长支脚
- ✓ 2个进风口Ø 200mm, 卡箍连接
- ✓ 包含启动装置和电机保护

尼的曼OMF, 油雾过滤器为处理持续运行中产生的大量纯油雾而设计, 为高效过滤且低维护成本而研发。

尼的曼标准OMF 2000 有三级滤芯单元, 其中上两级单元由尼的曼Nederman的FibreDrain® 专利技术的滤芯单元组成

尼的曼Nederman有各种不同类型的过滤单元来适配各种不同应用。第三级滤芯单元由一个H13的HEPA滤芯组成, 根据EN1822, 对MPPS的过滤效率达99.95%。所有尼的曼OMF 为竖直结构, 并且可以根据需要配置预过滤单元。OMF 2000 有内置离心风机。

OMF 2000

证书	CE
标准	2009/125/EC
噪音水平(分贝)	服务门端 50 Hz: 66 dB(A) @1,5 m 服务门端 60 Hz: 68 dB(A) @1,5 m
保护等级	IP55
过滤效能(%)	99.95
安装	室内
材料	金属板, 内外粉刷
工作压力(千帕)	Max 2500 Pa
性能(最大风量m³/h)	2000
电压(V)	230/400
频率(Hz)	50
电源相数	3
滤芯数量	3
安培数(安)	7,6 / 4,4
[ItemNoiselevel]	66
重量(公斤)	250
功率(kW)	2,2

Models

	Item number
	12400008 ^[1]

^[1] 加1个可选过滤项, 包括延长支脚

Accessories

	Accessory	Item number
	排泄泵箱, 50 Hz	12400054
	Drain container with piping	12400764
	预过滤器, ORF 610x610x96 G4I	12400039
	FibreDrain 过滤器 F66 OMF 1	12400009
	FibreDrain 过滤器 F66 OMF 2	12400010
	HEPA, DCM H13 595x595x100	12400012
	Outlet transition, Ø 200 mm, for OSF 1000 / OSF 1000-2 / OMF 1000-2 / OMF 2000	12400904
	Outlet transition, Ø 250 mm for OSF1000 / OSF1000-2 / OMF1000-2 / OMF2000	12400905
	Outlet transition, Ø 315 mm for OSF1000 / OSF1000-2 / OMF1000-2 / OMF2000	12400906
	FibreDrain Pumpbox KTF82-200 / 50Hz	12401330
	OSF/OMF Instruction manual for mounting system for electric components	12401342
	OMF/OSF/MQL mounting system for electrical components	12401341
	Frequency inverter with 2kPa pressure sensor. 2,2kW. IP66 enclosure	73008914

