

PRODUCT LEAFLET

NCF DX



NCF DX

ATEX认可的NCF Dx风机

尼的曼 NCF DX是强大的中央风机, 有着稳健的焊接钢结构。根据ATEX指令2014/34/EC 2组3类, NCF DX可用于处理22区的可燃粉尘。





NCF DX

证书	CE, EX
环境温度范围	-30 to +40 °C (-22 F to 104 F)
电压 (V)	400
频率 (Hz)	50
电源相数	3

Models

	Item number	安培数(安)	[ItemNoiselevel]	重量(公斤)	功率(kW)
	14530128	10,3	75 db(A) vid 4000 m³/h	110	5,5
	14530228	13,8	78 db(A) at 3500 m³/h	120	7,5
	14530328	20	77 db(A) at 6000 m³/h	205	11
	14530428	26,5	82 db(A) vid 8000 m³/h	232	15
	14530528	39,5/22,7	85 db(A) vid 10000 m³/h	319	22

Accessories

	Accessory	Item number
	进风口转接器, d250, 30/15, 40/25, 5	14374438
	进风口转接器, d400, 80/20, 120/25	14374440
	进风口转接器, d500, 120/15, 160/25	14374441
	出风口转接器, 288x205, d315, 30/15	14374442
	出风口转接器, 361x256, d400, 80/20	14374444
	出风口转接器, 453x322, d500, 120/15, 160/25	14374445
	出风口转接器, 256x183, d250, 50/25	14374446
	进风口活动转接器, d250, 30/15, 40/2	14374447
	进风口活动转接器, d400, 80/20, 120/	14374449
	进风口活动转接器, d500, 120/15, 160	14374450
	出风口活动转接器, 288x205, d315, 30	14374451
	出风口活动转接器, 361x256, d400, 80	14374453
	出风口活动转接器, 453x322, d500, 12	14374454
	出风口活动转接器, 256x183, d250, 50	14374455
	进风口安全网罩, d250, 30/15, 40/25	14374456
	进风口安全网罩, d400, 80/20, 120/25	14374458

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Accessories

	Accessory	Item number
	进风口安全网罩, d500, 120/15, 160/2	14374459
	出风口安全网罩, 30/15, 40/25	14374460
	出风口安全网罩, 80/20, 120/25	14374462
	出风口安全网罩, 120/15, 160/25	14374463
	出风口安全网罩, 50/25	14374464

