

PRODUCT LEAFLET

OSF 1500 FC

FibreDrain® 可持续运行的油雾收集设备



OSF 1500 FC

- ✓ 三级滤芯单元
- ✓ 观测每层滤芯单元的压强下降
- ✓ 紧凑的设计
- ✓ 2个进风口Ø 200mm, 卡箍连接
- ✓ 包含启动装置和电机保护

尼的曼Nederman OSF 油雾过滤器为处理持续运行中产生的大量纯油雾而设计, 为高效过滤且低维护成本而研发。

尼的曼标准Nederman OSF 1500 FC 有三级滤芯单元, 其中上面两级单元由尼的曼Nederman的FibreDrain®专利技术的滤芯单元组成

尼的曼Nederman有各种不同类型的过滤单元来适配各种不同应用。第三级滤芯单元由一个H13的HEPA滤芯组成, 根据EN1822, 对MPPS的过滤效率达99.95%。OSF 1500 FC有内置离心风机。

OSF 1500 FC

证书	CE
标准	2009/125/EC
噪音水平 (分贝)	服务门端 50 Hz: 67 dB(A) @1,5 m 服务门端 60 Hz: 69 dB(A) @1,5 m
保护等级	IP55
过滤效能 (%)	99.95
安装	室内
材料	金属板, 内外粉刷
清灰方式	自动排水
工作压力 (千帕)	Max 2500 Pa
性能 (最大风量 m ³ /h)	1500
工作温度	40 deg C (inbuilt fan)
电源相数	3

Models

	Item number	电压(V)	频率 (Hz)	滤芯数量	安培数(安)	[ItemNoiselevel]	重量(公斤)	功率(kW)
	12400874	230/400	50	3	7,6 / 4,4	67	270	2,2
	12401120	460	60	3	3,65	69	270	2,2
	12400875	230/400	50	3	7,6 / 4,4	67	270	2,2
	12401121	460	60	3	3,65	69	270	2,2
	12401223	460	60		7.9			2.2 kW
	12401224	460	60	3	7.9			2.2 kW

Accessories

	Accessory	Item number
	排泄泵箱, 50 Hz	12400054
	Drain container with piping	12400764
	FibreDrain 过滤器 F66 OSF 1	12400006
	FibreDrain 过滤器 F66 OSF 2	12400007
	Fibre Drain Filter 1 OSF; 600x300x292mm	12400164
	FibreDrain Filter 2 OSF; 600x300x292mm	12400169
	HEPA Filter H13; 610x610x150mm	12400852
	High capacity HEPA-filter kit for FC: 4 pcs distance holders and 1 pc HEPA filter 610x610x292mm	12400984
	Outlet connection OSF 1500FC - HEPA 610x610x292mm	12400761
	Outlet connection OSF 1500FC - HEPA 610x610x150mm	12400886
	FibreDrain Pumpbox KTF82-200 / 50Hz	12401330
	FibreDrain Pumpbox KTF81-220 / 60Hz	12401329
	Frequency inverter with 2kPa pressure sensor. 2,2kW. IP66 enclosure	73008914



