

PRODUCT LEAFLET

OSF 5x2000 SM

FibreDrain® 可持续运行的油雾收集设备



OSF 5x2000 SM

- ✓ 三级滤芯单元, 可选预过滤
- ✓ 观测每层滤芯单元的压强下降
- ✓ Drain: 4 off 1 1/2"
- ✓ Non-vibration fan suspension system

尼的曼Nederman OSF 油雾过滤器为处理持续运行中产生的大量纯油雾而设计, 为高效过滤且低维护成本而研发。

尼的曼标准 OSF 5x2000 SM 有三级滤芯单元, 其中上面两级单元由尼的曼Nederman的FibreDrain®专利技术的滤芯单元组成。尼的曼Nederman有各种不同类型的过滤单元来适配各种不同应用。第三级滤芯单元由一个H13的HEPA滤芯组成, 根据EN1822, 对MPPS的过滤效率达99.95%。所有尼的曼Nederman OSF为竖直结构, 并且可以根据需要配置预过滤单元。OSF 5x2000 SM 有内置离心风机。

OSF 5x2000 SM

证书	CE
标准	2009/125/EC
保护等级	IP55
过滤效能(%)	99.95
安装	室内
材料	金属板, 内外粉刷
清灰方式	自动排水
工作压力(千帕)	Max 4600 Pa
性能(最大风量m ³ /h)	10000
工作温度	60 deg C (limited by filter)
电压(V)	400/690
频率(Hz)	50
电源相数	3
滤芯数量	30
安培数(安)	26/15,1
颜色	NCS-S 1005 B20G
重量(公斤)	4270
功率(kW)	15

Models

	Item number
	12401147 ^[1]
	12401148 ^[1]

^[1] Plus 10可选过滤项

Accessories

	Accessory	Item number
	排泄泵箱, 50 Hz	12400054
	Drain container with piping	12400764
	预过滤器, ORF 610x610x96 G4I	12400039
	FibreDrain 过滤器 F66 OSF 1	12400006
	FibreDrain 过滤器 F66 OSF 2	12400007
	HEPA, DCM H13 595x595x100	12400012
	Inlet adapter OSF 5x2000	12401162
	Extension structure OSF 5x2000	12401167
	Fan enclosure 2 filters in depth	12401109
	OMF/OSF Silencer 90/Ø630	12401159
	FibreDrain Pumpbox KTF82-200 / 50Hz	12401330
	FibreDrain Pumpbox KTF81-220 / 60Hz	12401329
	OSF/OMF Instruction manual for mounting system for electric components	12401342
	OMF/OSF/MQL mounting system for electrical components	12401341









