

570A, Configurable

A powerful dust collector, excellent high vacuum for suction over long horizontal and vertical distances



570A, Configurable

- ✓ Silo system with large wheels
- ✓ Suitable for heavy and or abrasive material
- ✓ Robust and efficient self-cleaning filter

The configuration of modules will be similar to 570A which are aimed for the toughest applications, for example handling a lot of abrasive and heavy material. The robustness of the unit and the power from the reliable ejector makes the unit very suitable for many applications where many industrial vacuum cleaners can not be used. For example to collect blasting material in blasting hall, sand recovery in foundries etc.

Your unit can be configured to meet your specific demands. Different ejectors can be used depending on the demand but also the availability of compressed air. The ejector can be placed on a mobile silo with filter, with wheels and forklift slots. Nederman has a range of different discharge valves that can be fitted to the silo for easy discharge of the collected material. If handling larger quantities of material, Nederman recommends using a pre separator before the vacuum unit. See Nederman Engineering Guide for more information.

Use modules linked to 570A, configurable only. You may only choose ejectormodule, filtermodule, silomodule and discharge valve

1. Select ejectormodule depending on required vacuum and air flow.
2. Select filtermodule depending on filter capacity.
3. Select silomodule.
4. Select discharge valve.
5. Select cleaning equipment.

Choose how to control your butterfly valve:

1. Electric controlled - You need a namur valve, solenoid valve recommended for the ejector size you choose and a control box.
2. Air controlled - You need a namur valve.

Hose for air supply to the namur valve is not supplied by Nederman.

Control system with many different functions is available as an accessory

Ensure you meet all requirements for your modules.

570A, Configurable

证书	CE
清灰方式	压缩空气清灰
应用	粉尘, 颗粒物, 沙砾, 切屑

Models

	Item number	[ItemMaxAirFlow]	除尘器类型	滤芯数量
	43051000 ^[1]	330 Nm ³ /h		
	43051001 ^[1]	318 Nm ³ /h		
	43051002 ^[2]	690 Nm ³ /h		
	43051003 ^[2]	660 Nm ³ /h		
	43162101		蜡烛过滤器	70
	43164101		蜡烛过滤器	70
	43470034			

^[1] Recommended with filtermodule 43162101

^[2] Recommended with filtermodule 43164101

Accessories

	Accessory	Item number
	手动卸料阀	43630001
	平衡卸料阀	43630200
	气动卸料阀	43630100
	脉冲阀DN65	43632001
	脉冲阀DN80	43632100
	Manual butterfly valve kit, MFC	43630400
	Hose PU12-51 L=10m	43832600
	Hose PU12-51 L=5m	43832500
	PU管d51, 20m	43832300
	Hose PU12-51 L=7,5m w. couplings	43832102
	PU管d51, 10m	43832200
	Hose PU12-63 L=5m	43833200
	PU管d63, 10m	43833001

Accessories

	Accessory	Item number
	PU管d63, 20m	43833100
	PU管d76, 10m	43834200
	PU 管 d76 20m	43834300
	安装平板0802010 +0801020	43690001
	Control System for Ejectors	43220034
	通过 ATEX 认证的料桶液位计, 可在危险环境中进行安全监测, 并配有详细的用户手册说明。	40375269
	吸口装置总成 d51/500	42932100
	吸口装置总成 d51/400	42932800
	吸口装置总成 d51/400	42932300
	地板吸 头 d51/500	43840150
	地板吸 头 d51/400/65	43840250
	带毛刷地板吸 头 d51/400	43840550
	手持抽吸 头带毛刷d51	43860001

Accessories


	Accessory	Item number
	手持抽吸头PPd51	43861001
	手持锥形抽吸头d51	43862001
	抽排管防静电弯头 d51	43842150
	抽排管 d51 pehd-el 1m	43842001
	强力吸头带手柄 d51	43850150
	强力吸头 d51	43850001
	铁屑抽吸装置 d51 I1000	43851150
	铁屑抽吸装置 d51 I500	43851050
	木屑/金属屑 吸嘴, D=50mm	40150030
	地板吸头 d63/500	43840400
	强力吸头 d63	43850050
	Gulper head d63 hatch	43850051
	强力吸头带手柄 d63	43850200

Accessories


	Accessory	Item number
	铁屑抽吸装置 d63 11000	43851200
	抽排铝管弯头 d63	43843050
	钢旋转接头 d63	43843100
	抽排铝管 d63	43843001
	铁屑抽吸装置 d63 I500	43851100
	强力吸头 d76	43850100
	强力吸头带手柄 d76	43850250
	铁屑抽吸装置 d76 11000	43851250
	软管锥形变径 d76-63	43880350
	软管锥形变径 d76-51	43880300
	软管锥形变径 d63-51	43880250
	软管接头 d63	43880100
	软管接头 d50	43880050

Accessories

	Accessory	Item number
	软管锥形接头 d76	43880150
	控制器	43220001
	控制器 用于NE 22-76	43220026
	控制器 用于NE86-96	43222008
	地板吸 头 d63/600	43840450



Air Powered ejectors All performance data are based on 7 bar supply pressure



The height of the configuration is depending on filtermodule choosen.

